



PETRA ETHANOL FUEL TREATMENT AND STABILIZER

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Trade name : PETRA ETHANOL FUEL TREATMENT AND STABILIZER
Product code : PETRA 2005 (6 FL OZ/178 mL), 200555 (55 Gallons/208L)

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Ethanol Fuel Treatment

1.3. Details of the supplier of the safety data sheet

Petra Automotive Products, Inc.
11085 Regency Green Dr.
Cypress, TX 77429
T 713-856-5700

1.4. Emergency telephone number

Emergency number : CHEMTREC 24 Hour 1-800-424-9300, 1-703-527-3887 (International)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GHS US classification

Flammable liquids Category 4 H227 Combustible liquid
Carcinogenicity Category 1B H350 May cause cancer
Aspiration hazard Category 1 H304 May be fatal if swallowed and enters airways

Full text of H- and EUH-statements: see section 16

2.2. Label elements

GHS US labeling

Hazard pictograms (GHS US) :

Signal word (GHS US) : Danger

Hazard statements (GHS US) : H227 - Combustible liquid
H304 - May be fatal if swallowed and enters airways
H350 - May cause cancer

Precautionary statements (GHS US) : P201 - Obtain special instructions
P202 - Do not handle until all safety precautions have been read and understood.
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P280 - Wear protective gloves, protective clothing, eye protection, face protection
P301+P310 - If swallowed: Immediately call a poison control center, doctor, physician.
P308+P313 - If exposed or concerned: Get medical advice/attention.
P331 - Do NOT induce vomiting.
P370+P378 - In case of fire: See Section 5.1 Extinguishing Media
P403+P235 - Store in a well-ventilated place. Keep cool.
P405 - Store locked up.
P501 - Dispose of contents/container to appropriate waste disposal facility, in accordance with local, regional, national, international regulations.

2.3. Other hazards

Other hazards which do not result in classification : None under normal conditions.

2.4. Unknown acute toxicity (GHS US)

No data available

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

PETRA ETHANOL FUEL TREATMENT AND STABILIZER 6 FL.OZ.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Name	Product identifier	%	GHS US classification
Distillates (Petroleum), Hydrotreated Light	(CAS-No.) 64742-47-8	85 – 95	Asp. Tox. 1, H304
Solvent Naphtha (Petroleum), Light Aromatic	(CAS-No.) 64742-95-6	2.534 – 2.815	Flam. Liq. 2, H225 Muta. 1B, H340 Carc. 1B, H350 Asp. Tox. 1, H304
1,2,4-trimethylbenzene	(CAS-No.) 95-63-6	1.408 – 1.689	Flam. Liq. 3, H226 Acute Tox. 4 (Inhalation:vapour), H332 Skin Irrit. 2, H315 Eye Irrit. 2A, H319 STOT SE 3, H335
Mesitylene	(CAS-No.) 108-67-8	0.563 – 0.845	Flam. Liq. 3, H226 STOT SE 3, H335
1,2,3-Trimethylbenzene	(CAS-No.) 526-73-8	0.282 – 0.563	Flam. Liq. 3, H226
Stoddard Solvent	(CAS-No.) 8052-41-3	< 1	Flam. Liq. 3, H226 Muta. 1B, H340 Carc. 1B, H350 STOT RE 1, H372 Asp. Tox. 1, H304
2-Propanol	(CAS-No.) 67-63-0	0.113 – 0.169	Flam. Liq. 2, H225 Eye Irrit. 2A, H319 STOT SE 3, H336
Cumene	(CAS-No.) 98-82-8	< 0.056	Flam. Liq. 3, H226 Carc. 2, H351 STOT SE 3, H335 Asp. Tox. 1, H304
Xylene, Mixture of Isomers	(CAS-No.) 1330-20-7	< 0.011	Flam. Liq. 3, H226 Skin Irrit. 2, H315

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general : Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

First-aid measures after inhalation : Allow affected person to breathe fresh air. Allow the victim to rest.

First-aid measures after skin contact : Remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinse.

First-aid measures after eye contact : Rinse immediately with plenty of water. Obtain medical attention if pain, blinking or redness persists.

First-aid measures after ingestion : Rinse mouth. Do NOT induce vomiting. Immediately call a poison center or doctor/physician.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects : May cause genetic defects. May cause cancer.

Symptoms/effects after skin contact : May cause slight irritation. Itching. Red skin. Skin rash/inflammation.

Symptoms/effects after eye contact : May cause slight irritation. Irritation of the eye tissue. Inflammation/damage of the eye tissue. Redness of the eye tissue.

Symptoms/effects after ingestion : May be fatal if swallowed and enters airways.

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Foam. Dry powder. Carbon dioxide. Water spray. Sand.

Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Fire hazard : Combustible liquid.

Explosion hazard : May form flammable/explosive vapor-air mixture.

5.3. Advice for firefighters

Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire-fighting water from entering environment.

Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Remove ignition sources. Use special care to avoid static electric charges. No open flames. No smoking.

PETRA ETHANOL FUEL TREATMENT AND STABILIZER 6 FL.OZ.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

6.1.1. For non-emergency personnel

Protective equipment	: Gloves. Safety glasses.
Emergency procedures	: Evacuate unnecessary personnel.

6.1.2. For emergency responders

Protective equipment	: Equip cleanup crew with proper protection.
Emergency procedures	: Ventilate area.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

For containment	: Dam up the liquid spill. Contain released product, collect/pump into suitable containers. Plug the leak, cut off the supply.
Methods for cleaning up	: Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Store away from other materials.

6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed	: Handle empty containers with care because residual vapors are flammable. Keep away from heat, sparks, open flames, hot surfaces. - No smoking.
Precautions for safe handling	: Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapor. No open flames. No smoking. Obtain special instructions. Do not handle until all safety precautions have been read and understood. Eliminate all ignition sources if safe to do so.
Hygiene measures	: Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Do not eat, drink or smoke when using this product. Wash affected areas thoroughly after handling. Wash contaminated clothing before reuse. Always wash hands after handling the product. Remove contaminated clothes. Separate working clothes from town clothes. Launder separately. Take off immediately all contaminated clothing and wash it before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures	: Proper grounding procedures to avoid static electricity should be followed.
Storage conditions	: Keep only in the original container in a cool, well ventilated place away from : Keep container closed when not in use. Keep in fireproof place.
Incompatible products	: Strong bases. Strong acids.
Incompatible materials	: Sources of ignition. Direct sunlight. Heat sources.

7.3. Specific end use(s)

Follow Label Directions.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

PETRA ETHANOL FUEL TREATMENT AND STABILIZER 6 FL.OZ.	
No additional information available	
Solvent Naphtha (Petroleum), Light Aromatic (64742-95-6)	
No additional information available	
1,2,4-trimethylbenzene (95-63-6)	
USA - ACGIH - Occupational Exposure Limits	
ACGIH OEL TWA [ppm]	10 ppm
Mesitylene (108-67-8)	
USA - ACGIH - Occupational Exposure Limits	
ACGIH OEL TWA [ppm]	10 ppm 10 ppm
1,2,3-Trimethylbenzene (526-73-8)	
USA - ACGIH - Occupational Exposure Limits	
ACGIH OEL TWA [ppm]	10 ppm 10 ppm
Cumene (98-82-8)	
USA - ACGIH - Occupational Exposure Limits	
ACGIH OEL TWA [ppm]	5 ppm

PETRA ETHANOL FUEL TREATMENT AND STABILIZER 6 FL.OZ.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Xylene, Mixture of Isomers (1330-20-7)	
USA - ACGIH - Occupational Exposure Limits	
ACGIH OEL TWA [ppm]	20 ppm
Distillates (Petroleum), Hydrotreated Light (64742-47-8)	
USA - ACGIH - Occupational Exposure Limits	
ACGIH OEL TWA [ppm]	200 ppm 8 Hours
USA - NIOSH - Occupational Exposure Limits	
NIOSH REL (TWA)	100 mg/m ³
2-Propanol (67-63-0)	
USA - ACGIH - Occupational Exposure Limits	
ACGIH OEL TWA	980 mg/m ³
ACGIH OEL TWA [ppm]	400 ppm
ACGIH OEL STEL	1225 mg/m ³
ACGIH OEL STEL [ppm]	500 ppm
USA - OSHA - Occupational Exposure Limits	
OSHA PEL (TWA) [1]	980 mg/m ³
OSHA PEL (TWA) [2]	400 ppm
USA - NIOSH - Occupational Exposure Limits	
NIOSH REL (TWA)	980 mg/m ³
NIOSH REL TWA [ppm]	400 ppm
NIOSH REL (Ceiling)	1225 mg/m ³
NIOSH REL C [ppm]	500 ppm
Stoddard Solvent (8052-41-3)	
USA - ACGIH - Occupational Exposure Limits	
ACGIH OEL TWA [ppm]	100 ppm
USA - OSHA - Occupational Exposure Limits	
OSHA PEL (TWA) [1]	2900 mg/m ³
OSHA PEL (TWA) [2]	500 ppm

8.2. Appropriate engineering controls

Appropriate engineering controls : Local exhaust ventilation, vent hoods . Ensure good ventilation of the work station.
Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures/Personal protective equipment

Personal protective equipment:

Gloves. Safety glasses. Avoid all unnecessary exposure.

Materials for protective clothing:

Excellent resistance:

Hand protection:

Wear protective gloves

Eye protection:

Chemical goggles or safety glasses

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

Wear respiratory protection.

Personal protective equipment symbol(s):



PETRA ETHANOL FUEL TREATMENT AND STABILIZER 6 FL.OZ.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Other information:

Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Liquid.
Color	: Light yellow.
Odor	: Petroleum-like odour. Mild.
Odor threshold	: No data available
pH	: No data available
Relative evaporation rate (butyl acetate=1)	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: 65 °C
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability	: No data available
Vapor pressure	: No data available
Relative vapor density at 20 °C	: No data available
Relative density	: 0.82
Solubility	: Insoluble in water.
Partition coefficient n-octanol/water (Log Pow)	: No data available
Partition coefficient n-octanol/water (Log Kow)	: No data available
Viscosity, kinematic	: 1.92 cSt @ 40 deg C
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available
Explosion limits	: No data available

9.2. Other information

VOC content	: ≤ 5 %
-------------	---------

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

Combustible liquid. May form flammable/explosive vapor-air mixture.

10.3. Possibility of hazardous reactions

Not established.

10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures. Open flame. Overheating. Heat. Sparks.

10.5. Incompatible materials

Strong acids. Strong bases.

10.6. Hazardous decomposition products

Toxic fume. . Carbon monoxide. Carbon dioxide. May release flammable gases.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

1,2,4-trimethylbenzene (95-63-6)

LD50 oral rat	6000 mg/kg body weight (Equivalent or similar to EU Method B.1, Rat, Male, Experimental value, Oral, 014 day(s))
---------------	--

PETRA ETHANOL FUEL TREATMENT AND STABILIZER 6 FL.OZ.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

1,2,4-trimethylbenzene (95-63-6)	
LD50 dermal rat	3440 mg/kg (24 h, Rat, Male / female, Read-across, Dermal)
ATE US (oral)	6000 mg/kg body weight
ATE US (dermal)	3440 mg/kg body weight
ATE US (vapors)	11 mg/l/4h
Mesitylene (108-67-8)	
LD50 oral rat	6000 mg/kg body weight (Equivalent or similar to EU Method B.1, Rat, Male, Read-across, Oral, 14 day(s))
LD50 dermal rat	> 2000 mg/kg bw/day (24 h, Rat, Male / female, Read-across, Dermal)
ATE US (oral)	6000 mg/kg body weight
Cumene (98-82-8)	
LD50 oral rat	2700 mg/kg body weight (Equivalent or similar to OECD 401, Rat, Male / female, Experimental value, Oral, 014 day(s))
LD50 dermal rabbit	> 3160 mg/kg body weight (24 h, Rabbit, Male / female, Experimental value, Dermal, 14 day(s))
LC50 Inhalation - Rat	39 mg/l (4 h, Rat, Male, Experimental value, Inhalation (vapours), 14 day(s))
ATE US (oral)	2700 mg/kg body weight
ATE US (vapors)	39 mg/l/4h
ATE US (dust, mist)	39 mg/l/4h
Xylene, Mixture of Isomers (1330-20-7)	
LD50 oral rat	> 4000 mg/kg body weight (Equivalent or similar to EU Method B.1, Rat, Female, Experimental value, Oral, 14 day(s))
LD50 dermal rabbit	> 4200 mg/kg (Rabbit; Experimental value, Rabbit; Experimental value)
LC50 Inhalation - Rat	29.09 mg/l (Equivalent or similar to EU Method B.2, 4 h, Rat, Male, Experimental value, Inhalation (vapours), 14 day(s))
ATE US (vapors)	29.09 mg/l/4h
ATE US (dust, mist)	29.09 mg/l/4h
Distillates (Petroleum), Hydrotreated Light (64742-47-8)	
LD50 oral rat	> 5000 mg/kg body weight
LD50 dermal rabbit	> 2000 mg/kg
LC50 Inhalation - Rat	> 5.28 mg/l/4h Based on lack of mortality and systemic effects
2-Propanol (67-63-0)	
LD50 oral rat	5840 mg/kg body weight (Equivalent or similar to OECD 401, Rat, Experimental value, Oral, 14 day(s))
LD50 dermal rabbit	16400 ml/kg (Equivalent or similar to OECD 402, 24 h, Rabbit, Experimental value, Dermal, 14 day(s))
LC50 Inhalation - Rat [ppm]	> 10000 ppm (Equivalent or similar to OECD 403, 6 h, Rat, Male / female, Experimental value, Inhalation (vapours), 14 day(s))
ATE US (oral)	5840 mg/kg body weight
ATE US (dermal)	12890400 mg/kg body weight
Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Not classified
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: May cause cancer.
Solvent Naphtha (Petroleum), Light Aromatic (64742-95-6)	
IARC group	3 - Not classifiable
Cumene (98-82-8)	
IARC group	2B - Possibly carcinogenic to humans
National Toxicology Program (NTP) Status	Reasonably anticipated to be Human Carcinogen
Xylene, Mixture of Isomers (1330-20-7)	
IARC group	3 - Not classifiable
2-Propanol (67-63-0)	
IARC group	3 - Not classifiable
Reproductive toxicity	: Not classified
STOT-single exposure	: Not classified
1,2,4-trimethylbenzene (95-63-6)	
STOT-single exposure	May cause respiratory irritation.

PETRA ETHANOL FUEL TREATMENT AND STABILIZER 6 FL.OZ.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Mesitylene (108-67-8)	
STOT-single exposure	May cause respiratory irritation.
Cumene (98-82-8)	
STOT-single exposure	May cause respiratory irritation.
2-Propanol (67-63-0)	
STOT-single exposure	May cause drowsiness or dizziness.
STOT-repeated exposure	: Not classified
Stoddard Solvent (8052-41-3)	
STOT-repeated exposure	Causes damage to organs through prolonged or repeated exposure.
Aspiration hazard	: May be fatal if swallowed and enters airways.
Viscosity, kinematic	: 1.92 mm ² /s @ 40 deg C
Potential Adverse human health effects and symptoms	: Based on available data, the classification criteria are not met.
Symptoms/effects	: May cause genetic defects. May cause cancer.
Symptoms/effects after skin contact	: May cause slight irritation. Itching. Red skin. Skin rash/inflammation.
Symptoms/effects after eye contact	: May cause slight irritation. Irritation of the eye tissue. Inflammation/damage of the eye tissue. Redness of the eye tissue.
Symptoms/effects after ingestion	: May be fatal if swallowed and enters airways.

SECTION 12: Ecological information

12.1. Toxicity

1,2,4-trimethylbenzene (95-63-6)	
LC50 - Fish [1]	7.72 mg/l (96 h, Pimephales promelas, Flow-through system, Fresh water, Experimental value, Lethal)
Mesitylene (108-67-8)	
LC50 - Fish [1]	12.52 mg/l (96 h, Carassius auratus, Flow-through system, Fresh water, Experimental value, Nominal concentration)
ErC50 algae	53 mg/l (DIN 38412-9, 48 h, Desmodesmus subspicatus, Static system, Fresh water, Experimental value, Nominal concentration)
Cumene (98-82-8)	
LC50 - Fish [1]	4.8 mg/l (EPA OTS 797.1400, 96 h, Oncorhynchus mykiss, Flow-through system, Fresh water, Experimental value, GLP)
EC50 - Crustacea [1]	2.14 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna, Static system, Fresh water, Experimental value, Locomotor effect)
ErC50 algae	2.01 mg/l (EU Method C.3, 72 h, Desmodesmus subspicatus, Static system, Fresh water, Experimental value, GLP)
Xylene, Mixture of Isomers (1330-20-7)	
LC50 - Fish [1]	2.6 mg/l (OECD 203: Fish, Acute Toxicity Test, 96 h, Oncorhynchus mykiss, Static renewal, Fresh water, Read-across, Lethal)
ErC50 algae	4.36 mg/l (OECD 201: Alga, Growth Inhibition Test, 73 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, GLP)
2-Propanol (67-63-0)	
LC50 - Fish [1]	9640 – 10000 mg/l (Equivalent or similar to OECD 203, 96 h, Pimephales promelas, Flow-through system, Fresh water, Experimental value, Lethal)

12.2. Persistence and degradability

PETRA ETHANOL FUEL TREATMENT AND STABILIZER 6 FL.OZ.	
Persistence and degradability	Not established.
Solvent Naphtha (Petroleum), Light Aromatic (64742-95-6)	
Persistence and degradability	Not established.
1,2,4-trimethylbenzene (95-63-6)	
Persistence and degradability	Not readily biodegradable in water. Not established.
Chemical oxygen demand (COD)	0.44 g O ₂ /g substance
Mesitylene (108-67-8)	
Persistence and degradability	Biodegradable in the soil. Biodegradable in water. Not established.
Biochemical oxygen demand (BOD)	0.0957 g O ₂ /g substance
Chemical oxygen demand (COD)	0.319 g O ₂ /g substance
ThOD	3.19 g O ₂ /g substance

PETRA ETHANOL FUEL TREATMENT AND STABILIZER 6 FL.OZ.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

1,2,3-Trimethylbenzene (526-73-8)	
Persistence and degradability	Not readily biodegradable in water. Forming sediments in water. Non degradable in the soil. Adsorbs into the soil. Photodegradation in the air. Not established.
Cumene (98-82-8)	
Persistence and degradability	Not readily biodegradable in water. Not established.
Biochemical oxygen demand (BOD)	1.28 g O ₂ /g substance
Chemical oxygen demand (COD)	2.42 g O ₂ /g substance
ThOD	3.2 g O ₂ /g substance
Xylene, Mixture of Isomers (1330-20-7)	
Persistence and degradability	Biodegradable in the soil. Readily biodegradable in water.
Distillates (Petroleum), Hydrotreated Light (64742-47-8)	
Persistence and degradability	Not established.
2-Propanol (67-63-0)	
Persistence and degradability	Biodegradable in the soil. Biodegradable in the soil under anaerobic conditions. Readily biodegradable in water. Not established.
Biochemical oxygen demand (BOD)	1.19 g O ₂ /g substance
Chemical oxygen demand (COD)	2.23 g O ₂ /g substance
ThOD	2.4 g O ₂ /g substance
Stoddard Solvent (8052-41-3)	
Persistence and degradability	Not established.
12.3. Bioaccumulative potential	
PETRA ETHANOL FUEL TREATMENT AND STABILIZER 6 FL.OZ.	
Bioaccumulative potential	Not established.
Solvent Naphtha (Petroleum), Light Aromatic (64742-95-6)	
Partition coefficient n-octanol/water (Log Pow)	2.1 – 6
Bioaccumulative potential	Not established.
1,2,4-trimethylbenzene (95-63-6)	
BCF - Fish [1]	243 (Pimephales promelas, QSAR)
Partition coefficient n-octanol/water (Log Pow)	3.63 (Experimental value, KOWWIN)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4). Not established.
Mesitylene (108-67-8)	
BCF - Fish [1]	161 (Pimephales promelas, QSAR)
Partition coefficient n-octanol/water (Log Pow)	3.42 (Experimental value)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500). Not established.
1,2,3-Trimethylbenzene (526-73-8)	
BCF - Fish [1]	133 – 259 (Cyprinus carpio, Literature study)
Partition coefficient n-octanol/water (Log Pow)	3.66 (Experimental value)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500). Not established.
Cumene (98-82-8)	
BCF - Other aquatic organisms [1]	94.69 l/kg (BCFBaF v3.00, Calculated value)
Partition coefficient n-octanol/water (Log Pow)	3.55 (Experimental value, OECD 107: Partition Coefficient (n-octanol/water): Shake Flask Method, 23 °C)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4). Not established.
Xylene, Mixture of Isomers (1330-20-7)	
BCF - Fish [1]	7.2 – 25.9 (56 day(s), Oncorhynchus mykiss, Flow-through system, Fresh water, Read-across)
Partition coefficient n-octanol/water (Log Pow)	3.2 (Read-across, 20 °C)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).
Distillates (Petroleum), Hydrotreated Light (64742-47-8)	
Bioaccumulative potential	Not established.
2-Propanol (67-63-0)	
Partition coefficient n-octanol/water (Log Pow)	0.05 (Weight of evidence approach, 25 °C)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4). Not established.
Stoddard Solvent (8052-41-3)	
Partition coefficient n-octanol/water (Log Pow)	3.16 – 7.06
Bioaccumulative potential	Not established.
12.4. Mobility in soil	

PETRA ETHANOL FUEL TREATMENT AND STABILIZER 6 FL.OZ.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

1,2,4-trimethylbenzene (95-63-6)	
Surface tension	No data available in the literature
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	3.04 (log Koc, Calculated value)
Ecology - soil	Low potential for mobility in soil. May be harmful to plant growth, blooming and fruit formation.
Mesitylene (108-67-8)	
Surface tension	27.55 mN/m (25 °C, 100 vol %)
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	2.87 (log Koc, Calculated value)
Ecology - soil	Low potential for adsorption in soil. May be harmful to plant growth, blooming and fruit formation.
1,2,3-Trimethylbenzene (526-73-8)	
Ecology - soil	Adsorbs into the soil.
Cumene (98-82-8)	
Surface tension	28.2 mN/m (20 °C)
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	2.946 (log Koc, Calculated value)
Ecology - soil	Low potential for adsorption in soil.
Xylene, Mixture of Isomers (1330-20-7)	
Surface tension	28.01 – 29.76 mN/m (25 °C)
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	2.73 (log Koc, Equivalent or similar to OECD 121, Read-across)
Ecology - soil	Low potential for adsorption in soil. May be harmful to plant growth, blooming and fruit formation.
2-Propanol (67-63-0)	
Surface tension	No data available (test not performed)
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	0.185 – 0.541 (log Koc, SRC PCKOCWIN v2.0, Calculated value)
Ecology - soil	Highly mobile in soil.
Stoddard Solvent (8052-41-3)	
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	2.85 – 6.74 (log Koc)

12.5. Other adverse effects

Other information : Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product/Packaging disposal recommendations : Dispose in a safe manner in accordance with local/national regulations. Dispose of contents/container to appropriate waste disposal facility, in accordance with local, regional, national, international regulations.

Additional information : Handle empty containers with care because residual vapors are flammable.

Ecology - waste materials : Avoid release to the environment. Hazardous waste due to toxicity.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

Proper Shipping Name (DOT) : Not Regulated

Other information : No supplementary information available.

Transport by sea

Proper Shipping Name (IMDG) : Not Regulated

Air transport

Proper Shipping Name (IATA) : Not Regulated

PETRA ETHANOL FUEL TREATMENT AND STABILIZER 6 FL.OZ.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 15: Regulatory information

15.1. US Federal regulations

PETRA ETHANOL FUEL TREATMENT AND STABILIZER 6 FL.OZ.

SARA Section 311/312 Hazard Classes	Delayed (chronic) health hazard Fire hazard Immediate (acute) health hazard
-------------------------------------	---

Solvent Naphtha (Petroleum), Light Aromatic (64742-95-6)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

1,2,4-trimethylbenzene (95-63-6)

Listed on the United States TSCA (Toxic Substances Control Act) inventory
Subject to reporting requirements of United States SARA Section 313

SARA Section 313 - Emission Reporting	1 %
---------------------------------------	-----

Mesitylene (108-67-8)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

1,2,3-Trimethylbenzene (526-73-8)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Cumene (98-82-8)

Listed on the United States TSCA (Toxic Substances Control Act) inventory
Subject to reporting requirements of United States SARA Section 313

CERCLA RQ	5000 lb
SARA Section 311/312 Hazard Classes	Fire hazard Immediate (acute) health hazard Delayed (chronic) health hazard
SARA Section 313 - Emission Reporting	1 %

Xylene, Mixture of Isomers (1330-20-7)

Listed on the United States TSCA (Toxic Substances Control Act) inventory
Subject to reporting requirements of United States SARA Section 313

CERCLA RQ	100 lb
SARA Section 311/312 Hazard Classes	Fire hazard
SARA Section 313 - Emission Reporting	1 %

Distillates (Petroleum), Hydrotreated Light (64742-47-8)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard Delayed (chronic) health hazard
-------------------------------------	--

2-Propanol (67-63-0)

Listed on the United States TSCA (Toxic Substances Control Act) inventory
Subject to reporting requirements of United States SARA Section 313

SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard Fire hazard
SARA Section 313 - Emission Reporting	1 %

Stoddard Solvent (8052-41-3)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

SARA Section 311/312 Hazard Classes	Delayed (chronic) health hazard Fire hazard Immediate (acute) health hazard
-------------------------------------	---

15.2. International regulations

CANADA

PETRA ETHANOL FUEL TREATMENT AND STABILIZER 6 FL.OZ.

WHMIS Classification	Class B Division 3 - Combustible Liquid
----------------------	---

Solvent Naphtha (Petroleum), Light Aromatic (64742-95-6)

Listed on the Canadian DSL (Domestic Substances List)

1,2,4-trimethylbenzene (95-63-6)

Listed on the Canadian DSL (Domestic Substances List)

WHMIS Classification	Class B Division 3 - Combustible Liquid Class D Division 1 Subdivision B - Toxic material causing immediate and serious toxic effects Class D Division 2 Subdivision B - Toxic material causing other toxic effects
----------------------	---

Mesitylene (108-67-8)

Listed on the Canadian DSL (Domestic Substances List)

PETRA ETHANOL FUEL TREATMENT AND STABILIZER 6 FL.OZ.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

1,2,3-Trimethylbenzene (526-73-8)

Listed on the Canadian DSL (Domestic Substances List)

Cumene (98-82-8)

Listed on the Canadian DSL (Domestic Substances List)

WHMIS Classification

Class B Division 2 - Flammable Liquid

Class D Division 2 Subdivision A - Very toxic material causing other toxic effects

Xylene, Mixture of Isomers (1330-20-7)

Listed on the Canadian DSL (Domestic Substances List)

Distillates (Petroleum), Hydrotreated Light (64742-47-8)

Listed on the Canadian DSL (Domestic Substances List)

WHMIS Classification

Uncontrolled product according to WHMIS classification criteria

2-Propanol (67-63-0)

Listed on the Canadian DSL (Domestic Substances List)

WHMIS Classification

Class B Division 2 - Flammable Liquid

Stoddard Solvent (8052-41-3)

Listed on the Canadian DSL (Domestic Substances List)

WHMIS Classification

Class B Division 3 - Combustible Liquid

Class D Division 2 Subdivision B - Toxic material causing other toxic effects

EU-Regulations

1,2,4-trimethylbenzene (95-63-6)

Mesitylene (108-67-8)

1,2,3-Trimethylbenzene (526-73-8)

Cumene (98-82-8)

Xylene, Mixture of Isomers (1330-20-7)

Distillates (Petroleum), Hydrotreated Light (64742-47-8)

2-Propanol (67-63-0)

Stoddard Solvent (8052-41-3)

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Not classified

Classification according to Directive 67/548/EEC [DSD] or 1999/45/EC [DPD]

15.2.2. National regulations

1,2,4-trimethylbenzene (95-63-6)

Mesitylene (108-67-8)

1,2,3-Trimethylbenzene (526-73-8)

Cumene (98-82-8)

Listed on IARC (International Agency for Research on Cancer)

Listed as carcinogen on NTP (National Toxicology Program)

Listed on EPA Hazardous Air Pollutant (HAPS)

Xylene, Mixture of Isomers (1330-20-7)

Listed on EPA Hazardous Air Pollutant (HAPS)

Distillates (Petroleum), Hydrotreated Light (64742-47-8)

2-Propanol (67-63-0)

Stoddard Solvent (8052-41-3)

15.3. US State regulations

PETRA ETHANOL FUEL TREATMENT AND STABILIZER 6 FL.OZ.()

U.S. - California - Proposition 65 - Carcinogens List	No
U.S. - California - Proposition 65 - Developmental Toxicity	No
U.S. - California - Proposition 65 - Reproductive Toxicity - Female	No
U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No

PETRA ETHANOL FUEL TREATMENT AND STABILIZER 6 FL.OZ.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Solvent Naphtha (Petroleum), Light Aromatic (64742-95-6)

U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)
No	No	No	No	

1,2,4-trimethylbenzene (95-63-6)

U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)
No	No	No	No	

Mesitylene (108-67-8)

U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)
No	No	No	No	

1,2,3-Trimethylbenzene (526-73-8)

U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)
No	No	No	No	

Cumene (98-82-8)

U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)
Yes	No	No	No	

Xylene, Mixture of Isomers (1330-20-7)

U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)
No	No	No	No	

Distillates (Petroleum), Hydrotreated Light (64742-47-8)

U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)
No	No	No	No	

2-Propanol (67-63-0)

U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)
No	No	No	No	

Stoddard Solvent (8052-41-3)

U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)
No	No	No	No	

1,2,4-trimethylbenzene (95-63-6)

State or local regulations				
U.S. - Delaware - Pollutant Discharge Requirements - Reportable Quantities U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List				

PETRA ETHANOL FUEL TREATMENT AND STABILIZER 6 FL.OZ.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

1,2,4-trimethylbenzene (95-63-6)

U.S. – New York City – Right to Know Hazardous Substances List
U.S. - Pennsylvania - RTK (Right to Know) List

Mesitylene (108-67-8)

State or local regulations

U.S. – New York City – Right to Know Hazardous Substances List

Cumene (98-82-8)

State or local regulations

U.S. - Delaware - Pollutant Discharge Requirements - Reportable Quantities
U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Acceptable Ambient Concentrations
U.S. - Massachusetts - Right To Know List
U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. – New York City – Right to Know Hazardous Substances List
U.S. - Pennsylvania - RTK (Right to Know) List

Xylene, Mixture of Isomers (1330-20-7)

State or local regulations

U.S. - Delaware - Pollutant Discharge Requirements - Reportable Quantities
U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Acceptable Ambient Concentrations
U.S. - Massachusetts - Right To Know List
U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. – New York City – Right to Know Hazardous Substances List
U.S. - Pennsylvania - RTK (Right to Know) List

2-Propanol (67-63-0)

State or local regulations

U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Acceptable Ambient Concentrations
U.S. - Massachusetts - Right To Know List
U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. – New York City – Right to Know Hazardous Substances List
U.S. - Pennsylvania - RTK (Right to Know) List

Stoddard Solvent (8052-41-3)

State or local regulations

U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Acceptable Ambient Concentrations
U.S. - Massachusetts - Right To Know List
U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. – New York City – Right to Know Hazardous Substances List
U.S. - Pennsylvania - RTK (Right to Know) List

SECTION 16: Other information

Other information : None.

Full text of H-phrases:

H225	Highly flammable liquid and vapor
H226	Flammable liquid and vapor
H227	Combustible liquid
H304	May be fatal if swallowed and enters airways
H315	Causes skin irritation
H319	Causes serious eye irritation
H332	Harmful if inhaled
H335	May cause respiratory irritation
H336	May cause drowsiness or dizziness
H340	May cause genetic defects
H350	May cause cancer
H351	Suspected of causing cancer
H372	Causes damage to organs through prolonged or repeated exposure

NFPA health hazard


: 2 - Materials that, under emergency conditions, can cause temporary incapacitation or residual injury.

NFPA fire hazard

: 2 - Materials that must be moderately heated or exposed to relatively high ambient temperatures before ignition can occur.

NFPA reactivity

: 0 - Material that in themselves are normally stable, even under fire conditions.



PETRA ETHANOL FUEL TREATMENT AND STABILIZER 6 FL.OZ.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Hazard Rating

Health	: 2 Moderate Hazard - Temporary or minor injury may occur
Flammability	: 2 Moderate Hazard
Physical	: 0 Minimal Hazard
Personal protection	: B

The Supplier identified in Section 1 of this SDS has evaluated this product and certifies it to be labeled and packaged in compliance with the applicable provisions of the Federal Hazardous Substance Act as stated in 16 CFR 1500 and enforced by the Consumer Product Safety Commission, and where applicable the products that require Child Resistant Closures are packaged in accordance with the Poison Prevention Packaging Act as stated in 16 CFR 1700 and enforced by the Consumer Product Safety Commission. All closures have been tested in accordance with the latest protocols. No other testing is required to certify compliance with the above. The date of manufacture is stamped on the product

Disclaimer: The information and recommendations contained herein are based upon tests believed to be reliable. However, the manufacturer/distributor of this product does not guarantee their accuracy or completeness NOR SHALL ANY OF THIS INFORMATION CONSTITUTE A WARRANTY, WHETHER EXPRESSED OR IMPLIED, AS TO THE SAFETY OF THE GOODS, THE MERCHANTABILITY OF THE GOODS, OR THE FITNESS OF THE GOODS FOR A PARTICULAR PURPOSE. Adjustment to conform to actual conditions of usage may be required. The manufacturer/distributor assumes no responsibility for results obtained or for incidental or consequential damages, including lost profits, arising from the use of these data. No warranty against infringement of any patent, copyright or trademark is made or implied.