



# PETRA SYNTHETIC DOT 4 BRAKE FLUID

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Version: 1.3

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product form : Mixture  
Trade name : PETRA SYNTHETIC DOT 4 BRAKE FLUID  
Product code : 6412, 6432, 6464

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Brake Fluid

#### 1.3. Details of the supplier of the safety data sheet

Petra Oil Company  
11085 Regency Green Drive  
Cypress, TX 77429  
T 713-856-5700

#### 1.4. Emergency telephone number

Emergency number : CHEMTREC 24 Hour 1-800-424-9300, 1-703-527-3887 (International)

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### GHS-US classification

Skin Irrit. 2 H315  
Eye Dam. 1 H318  
STOT RE 2 H373

Full text of H statements : see section 16

#### 2.2. Label elements

##### GHS-US labeling

Hazard pictograms (GHS-US) :



GHS05



GHS08

Signal word (GHS-US) : Danger

Hazard statements (GHS-US) :  
H315 - Causes skin irritation  
H318 - Causes serious eye damage  
H373 - May cause damage to organs through prolonged or repeated exposure

Precautionary statements (GHS-US) :  
P260 - Do not breathe dust,fumes,gas,mist,vapor spray  
P264 - Wash affected areas thoroughly after handling  
P280 - Wear protective gloves,protective clothing,eye protection,face protection  
P302+P352 - If on skin: Wash with plenty of soap and water  
P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
P310 - Immediately call a poison center,doctor, physician  
P314 - Get medical advice/attention if you feel unwell  
P321 - Specific treatment: See section 4.1 on SDS  
P332+P313 - If skin irritation occurs: Get medical advice/attention  
P362+P364 - Take off contaminated clothing and wash it before reuse  
P501 - Dispose of contents/container to appropriate waste disposal facility, in accordance with local, regional, national, international regulations.

#### 2.3. Other hazards

Other hazards not contributing to the classification : None under normal conditions.

#### 2.4. Unknown acute toxicity (GHS US)

No data available

### SECTION 3: Composition/Information on ingredients

#### 3.1. Substances

Not applicable

#### 3.2. Mixtures

# PETRA SYNTHETIC DOT 4 BRAKE FLUID

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

| Name   | Product identifier  | %       | GHS-US classification   |
|--|---------------------|---------|---|
| Triethyleneglycol Monoethyl Ether                    | (CAS No) 112-50-5   | 35 - 40 | Not classified  |
| Butyl Triglycoether                                  | (CAS No) 143-22-6   | 10 - 30 | Eye Dam. 1, H318  |
| Triethylene Glycol Monomethyl Ether                  | (CAS No) 112-35-6   | 5 - 25  | Not classified  |
| Diethylene Glycol                                    | (CAS No) 111-46-6   | 5 - 20  | Acute Tox. 4 (Oral), H302<br>STOT RE 2, H373  |
| Methoxypolyethyleneglycols                           | (CAS No) 9004-74-4  | 0 - 15  | Not classified  |
| Poly(oxy-1,2-ethanediyl), alpha-butyl-omega-hydroxy- | (CAS No) 9004-77-7  | 0 - 15  | Not classified  |
| Polyethylene Glycol                                  | (CAS No) 25322-68-3 | 6 - 14  | Not classified  |
| 2-(2-Butoxyethoxy) Ethanol                           | (CAS No) 112-34-5   | 5 - 10  | Eye Irrit. 2, H319  |
| Triethyleneglycol                                    | (CAS No) 112-27-6   | 0 - 10  | Not classified  |
| Diethyleneglycolmonoethyl Ether                      | (CAS No) 111-90-0   | 3 - 5   | Eye Irrit. 2A, H319   |
| Diethanolamine                                       | (CAS No) 111-42-2   | 0 - 1   | Acute Tox. 4 (Oral), H302<br>Skin Irrit. 2, H315<br>Eye Dam. 1, H318<br>STOT RE 2, H373 |
| Diisopropanolamine                                   | (CAS No) 110-97-4   | 0 - 1   | Eye Irrit. 2, H319  |

The exact percentage is a trade secret.

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

- First-aid measures general : Never give anything by mouth to an unconscious person. IF exposed or concerned: Get medical advice/attention.
- First-aid measures after inhalation : Allow victim to breathe fresh air. Allow the victim to rest. Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.
- First-aid measures after skin contact : Wash with plenty of soap and water. Wash contaminated clothing before reuse. If skin irritation occurs: Get medical advice/attention.
- First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center or doctor/physician.
- First-aid measures after ingestion : Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention. Call a POISON CENTER or doctor/physician if you feel unwell.

#### 4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/injuries : Causes damage to organs. Suspected of damaging fertility or the unborn child.
- Symptoms/injuries after inhalation : Danger of serious damage to health by prolonged exposure through inhalation. Harmful if inhaled.
- Symptoms/injuries after skin contact : May cause moderate irritation. Itching. Red skin. Skin rash/inflammation. Causes skin irritation.
- Symptoms/injuries after eye contact : Irritation of the eye tissue. Inflammation/damage of the eye tissue. Redness of the eye tissue. Causes serious eye damage.
- Symptoms/injuries after ingestion : Swallowing a small quantity of this material will result in serious health hazard.

#### 4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

- Suitable extinguishing media : Foam. Dry powder. Carbon dioxide. Water spray. Sand.
- Unsuitable extinguishing media : Do not use a heavy water stream.

#### 5.2. Special hazards arising from the substance or mixture

No additional information available

#### 5.3. Advice for firefighters

- Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire-fighting water from entering environment.
- Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

- General measures : Remove ignition sources. Use special care to avoid static electric charges.

##### 6.1.1. For non-emergency personnel

- Protective equipment : Gloves. Safety glasses.
- Emergency procedures : Evacuate unnecessary personnel.

##### 6.1.2. For emergency responders

- Protective equipment : Equip cleanup crew with proper protection.

# PETRA SYNTHETIC DOT 4 BRAKE FLUID

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Emergency procedures : Ventilate area.

### 6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

### 6.3. Methods and material for containment and cleaning up

For containment : Dam up the liquid spill. Plug the leak, cut off the supply. Contain released product, pump into suitable containers.

Methods for cleaning up : Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Store away from other materials.

### 6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Precautions for safe handling : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapor. Use only outdoors or in a well-ventilated area. Avoid breathing dust,fume,gas,mist,vapor spray. Obtain special instructions . Do not handle until all safety precautions have been read and understood.

Hygiene measures : Do not eat, drink or smoke when using this product. Wash affected areas thoroughly after handling. Wash contaminated clothing before reuse. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Take off immediately all contaminated clothing and wash it before reuse. Observe normal hygiene standards. Keep container tightly closed. Always wash hands after handling the product. Remove contaminated clothes. Separate working clothes from town clothes. Launder separately.

### 7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Proper grounding procedures to avoid static electricity should be followed.

Storage conditions : Keep only in the original container in a cool, well ventilated place away from : Keep container closed when not in use.

Incompatible products : Strong bases. Strong acids.

Incompatible materials : Sources of ignition. Direct sunlight.

Storage area : Keep only in the original container.

Special rules on packaging : Keep only in original container.

### 7.3. Specific end use(s)

Follow Label Directions.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

| 2-(2-Butoxyethoxy) Ethanol (112-34-5) |                                |  |
|---------------------------------------|--------------------------------|--|
| USA ACGIH                             | ACGIH TWA (ppm)                | 10 ppm (Diethylene glycol monobutyl ether; USA; Time-weighted average exposure limit 8 h; TLV - Adopted Value; Inhalable fraction and vapor) |
| Diethanolamine (111-42-2)             |                                |  |
| USA ACGIH                             | ACGIH TWA (mg/m <sup>3</sup> ) | 1 mg/m <sup>3</sup> (Diethanolamine; USA; Time-weighted average exposure limit 8 h; TLV - Adopted Value; Inhalable fraction and vapor)       |

### 8.2. Exposure controls

Appropriate engineering controls : Local exhaust ventilation, vent hoods . Ensure good ventilation of the work station.

Personal protective equipment : Gloves. Safety glasses. Avoid all unnecessary exposure.



Materials for protective clothing : GIVE EXCELLENT RESISTANCE:

Hand protection : Wear protective gloves.

Eye protection : Chemical goggles or safety glasses.

Skin and body protection : Wear suitable protective clothing.

Respiratory protection : Wear appropriate mask.

Environmental exposure controls : Avoid release to the environment.

Consumer exposure controls : Avoid contact during pregnancy/while nursing.

Other information : Do not eat, drink or smoke during use.

# PETRA SYNTHETIC DOT 4 BRAKE FLUID

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### SECTION 9: Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

|   |  |
|---|--|
| Physical state                              | : Liquid                                     |
| Appearance                                  | : Liquid.                                    |
| Color                                       | : Amber. Yellow.                             |
| Odor  | : Mild . Ammoniacal.                         |
| Odor threshold                              | : No data available                          |
| pH  | : 9 - 11                                     |
| Relative evaporation rate (butyl acetate=1) | : No data available                          |
| Melting point                               | : < -59 °C                                   |
| Freezing point                              | : No data available                          |
| Boiling point                               | : > 230 °C                                   |
| Flash point                                 | : 203 °C                                     |
| Auto-ignition temperature                   | : No data available                          |
| Decomposition temperature                   | : No data available                          |
| Flammability (solid, gas)                   | : No data available                          |
| Vapor pressure                              | : < 0.01 mm Hg Estimated                     |
| Relative vapor density at 20 °C             | : > 10                                       |
| Relative density                            | : 1.03 - 1.08                                |
| Solubility                                  | : Soluble in water.<br>Water: 100% Estimated |
| Log Pow                                     | : No data available                          |
| Log Kow                                     | : No data available                          |
| Viscosity, kinematic                        | : < 1500 cSt                                 |
| Viscosity, dynamic                          | : No data available                          |
| Explosive properties                        | : No data available                          |
| Oxidizing properties                        | : No data available                          |
| Explosion limits                            | : No data available                          |

#### 9.2. Other information

|             |       |
|-------------|-------|
| VOC content | : 0 % |
|-------------|-------|

### SECTION 10: Stability and reactivity

#### 10.1. Reactivity

No additional information available

#### 10.2. Chemical stability

Not established.

#### 10.3. Possibility of hazardous reactions

Not established.

#### 10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures.

#### 10.5. Incompatible materials

Oxidizing agent. Strong acids. Strong bases.

#### 10.6. Hazardous decomposition products

Toxic fume. . Carbon monoxide. Carbon dioxide.

### SECTION 11: Toxicological information

#### 11.1. Information on toxicological effects

|                |                  |
|----------------|------------------|
| Acute toxicity | : Not classified |
|----------------|------------------|

| Triethyleneglycol Monoethyl Ether (112-50-5) |  |
|--|--|
| LD50 oral rat                                | 7750 mg/kg (Rat)   |
| LD50 dermal rabbit                           | 8168 mg/kg (Rabbit)  |
| Butyl Triglycoether (143-22-6)               |  |
| LD50 oral rat                                | 5170 mg/kg body weight (Rat; according to BASF-internal standards; Experimental value) |
| LD50 dermal rabbit                           | 3540 mg/kg body weight (Rabbit; Experimental value; OECD 402: Acute Dermal Toxicity)   |

# PETRA SYNTHETIC DOT 4 BRAKE FLUID

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

|   |  |
|---|--|
| <b>Polyethylene Glycol (25322-68-3)</b>                                 |  |
| LD50 oral rat   | 30200 mg/kg (Rat, Literature study)  |
| LD50 dermal rabbit  | > 20000 mg/kg (Rabbit, Inconclusive, insufficient data)  |
| ATE CLP (oral)  | 30200 mg/kg body weight  |
| <b>2-(2-Butoxyethoxy) Ethanol (112-34-5)</b>                            |  |
| LD50 dermal rabbit  | 2764 mg/kg body weight (Rabbit; Experimental value; Equivalent or similar to OECD 402)                                       |
| <b>Diethylene Glycol (111-46-6)</b>                                     |  |
| LD50 dermal rabbit  | 11890 mg/kg (Rabbit)   |
| <b>Diethyleneglycolmonoethyl Ether (111-90-0)</b>                       |  |
| LD50 oral rat   | 5445 mg/kg (Rat)   |
| LD50 dermal rat   | 5940 mg/kg (Rat)   |
| LD50 dermal rabbit  | > 5000 mg/kg (Rabbit)  |
| LC50 inhalation rat (mg/l)  | > 5.2 mg/l/4h (Rat)  |
| <b>Triethyleneglycol (112-27-6)</b>                                     |  |
| LD50 oral rat   | > 5000 mg/kg (Rat)   |
| LD50 dermal rabbit  | > 5000 mg/kg (Rabbit)  |
| <b>Methoxypolyethyleneglycols (9004-74-4)</b>                           |  |
| LD50 oral rat   | > 2000 mg/kg body weight (Rat)   |
| LD50 dermal rabbit  | > 2000 mg/kg body weight (Rabbit)  |
| <b>Poly(oxy-1,2-ethanediyl), alpha-butyl-omega-hydroxy- (9004-77-7)</b> |  |
| LD50 oral rat   | > 2000 mg/kg body weight (OECD 401: Acute Oral Toxicity, Rat, Male/female, Experimental value)                               |
| LD50 dermal rabbit  | 3540 mg/kg body weight (Modification of Draize 1959 method, 24 h, Rabbit, Male, Read-across)                                 |
| ATE CLP (dermal)  | 3540 mg/kg body weight   |
| <b>Triethylene Glycol Monomethyl Ether (112-35-6)</b>                   |  |
| LD50 oral rat   | 11865 mg/kg (Rat)  |
| LD50 dermal rabbit  | 7455 mg/kg (Rabbit)  |
| <b>Diisopropanolamine (110-97-4)</b>                                    |  |
| LD50 oral rat   | 4765 mg/kg (Rat)   |
| LD50 dermal rat   | 16000 mg/kg (Rat)  |
| LD50 dermal rabbit  | 8000 mg/kg (Rabbit)  |
| <b>Diethanolamine (111-42-2)</b>  |  |
| LD50 oral rat   | 620 mg/kg (Rat)  |
| LD50 dermal rabbit  | 7640 mg/kg (Rabbit)  |
| Skin corrosion/irritation   | : Causes skin irritation.<br>pH: 9 - 11  |
| Serious eye damage/irritation   | : Causes serious eye damage.<br>pH: 9 - 11   |
| Respiratory or skin sensitization                                       | : Not classified   |
| Germ cell mutagenicity  | : Not classified Based on available data, the classification criteria are not met  |
| Carcinogenicity   | : Not classified   |
| <b>Diethanolamine (111-42-2)</b>  |  |
| IARC group  | 3  |
| Reproductive toxicity   | : Not classified   |
| Specific target organ toxicity – single exposure                        | : Not classified   |
| Specific target organ toxicity – repeated exposure                      | : May cause damage to organs through prolonged or repeated exposure.   |
| Aspiration hazard   | : Not classified   |
| Potential Adverse human health effects and symptoms                     | : Based on available data, the classification criteria are not met. Harmful if swallowed. Harmful if inhaled.                |
| Symptoms/injuries after inhalation                                      | : Danger of serious damage to health by prolonged exposure through inhalation. Harmful if inhaled.                           |
| Symptoms/injuries after skin contact                                    | : May cause moderate irritation. Itching. Red skin. Skin rash/inflammation. Causes skin irritation.                          |
| Symptoms/injuries after eye contact                                     | : Irritation of the eye tissue. Inflammation/damage of the eye tissue. Redness of the eye tissue. Causes serious eye damage. |
| Symptoms/injuries after ingestion                                       | : Swallowing a small quantity of this material will result in serious health hazard.   |

# PETRA SYNTHETIC DOT 4 BRAKE FLUID

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### SECTION 12: Ecological information

#### 12.1. Toxicity

|   |  |
|---|--|
| <b>Triethyleneglycol Monoethyl Ether (112-50-5)</b>                     |  |
| LC50 fish 1   | > 10000 mg/l (LC50; 96 h)  |
| EC50 Daphnia 1  | > 10000 mg/l (LC50; 48 h)  |
| <b>Butyl Triglycoether (143-22-6)</b>                                   |  |
| LC50 fish 1   | 2200/2400,LC50; DIN 38412-15; 96 h; Leuciscus idus; Static system; Fresh water; Experimental value                                       |
| EC50 Daphnia 1  | > 500 mg/l (EC50; EU Method C.2; 48 h; Daphnia magna; Static system; Fresh water; Experimental value)                                    |
| Threshold limit algae 1   | 62.5 mg/l (NOEC; DIN 38412-9; 72 h; Desmodesmus subspicatus; Static system; Fresh water; Experimental value)                             |
| <b>Polyethylene Glycol (25322-68-3)</b>                                 |  |
| LC50 fish 1   | > 100 mg/l (OECD 203: Fish, Acute Toxicity Test, 96 h, Poecilia reticulata, Static system, Fresh water, Experimental value)              |
| LC50 other aquatic organisms 1  | > 1000 mg/l (96 h)   |
| <b>2-(2-Butoxyethoxy) Ethanol (112-34-5)</b>                            |  |
| LC50 fish 1   | 1300 mg/l (LC50; Equivalent or similar to OECD 203; 96 h; Lepomis macrochirus; Static system; Fresh water; Experimental value)           |
| EC50 Daphnia 1  | 4950 mg/l (EC50; Equivalent or similar to OECD 202; 48 h; Daphnia magna; Static system; Fresh water; Experimental value)                 |
| Threshold limit algae 1   | > 100 mg/l (EC50; OECD 201: Alga, Growth Inhibition Test; 96 h; Desmodesmus subspicatus; Static system; Fresh water; Experimental value) |
| <b>Diethylene Glycol (111-46-6)</b>                                     |  |
| LC50 fish 1   | > 5000 ppm (LC50; 24 h)  |
| EC50 Daphnia 1  | > 10000 mg/l (EC50; 24 h)  |
| <b>Diethyleneglycolmonoethyl Ether (111-90-0)</b>                       |  |
| LC50 fish 1   | 12900 mg/l (LC50; 96 h; Salmo gairdneri)   |
| EC50 Daphnia 1  | 3940 mg/l (EC50; 48 h)   |
| <b>Triethyleneglycol (112-27-6)</b>                                     |  |
| EC50 Daphnia 1  | 42426 mg/l (EC50; 48 h)  |
| LC50 fish 2   | 61000 mg/l (LC50; 96 h; Lepomis macrochirus)   |
| Threshold limit algae 2   | > 10000 mg/l (EC0; 168 h)  |
| <b>Poly(oxy-1,2-ethanediyl), alpha-butyl-omega-hydroxy- (9004-77-7)</b> |  |
| LC50 fish 1   | > 1800 mg/l (OECD 203: Fish, Acute Toxicity Test, 96 h, Scophthalmus maximus, Semi-static system, Salt water, Experimental value)        |
| EC50 Daphnia 1  | > 3200 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna, Semi-static system, Fresh water, Experimental value)  |
| ErC50 (algae)   | 2490 mg/l (OECD 201: Alga, Growth Inhibition Test, 72 h, Selenastrum capricornutum, Static system, Fresh water, Read-across)             |
| <b>Triethylene Glycol Monomethyl Ether (112-35-6)</b>                   |  |
| LC50 fish 1   | > 5000 mg/l (LC50; 96 h)   |
| EC50 Daphnia 1  | > 10000 mg/l (LC50; 48 h)  |
| Threshold limit algae 1   | > 500 mg/l (EC50; 72 h)  |
| <b>Diisopropanolamine (110-97-4)</b>                                    |  |
| LC50 fish 1   | 1000 - 2200 mg/l (LC50; OECD 203: Fish, Acute Toxicity Test; 96 h; Brachydanio rerio)  |
| EC50 Daphnia 2  | 277.7 mg/l (EC50; 48 h)  |
| Threshold limit algae 1   | 270 mg/l (EC50; 72 h)  |
| <b>Diethanolamine (111-42-2)</b>  |  |
| LC50 fish 1   | 1664 mg/l (LC50; 96 h; Pimephales promelas)  |
| EC50 Daphnia 2  | 55 mg/l (EC50; 48 h)   |

#### 12.2. Persistence and degradability

|   |   |
|---|---|
| <b>PETRA SYNTHETIC DOT 4 BRAKE FLUID 12 FL.OZ.</b>  |   |
| Persistence and degradability                       | Not established.  |
| <b>Triethyleneglycol Monoethyl Ether (112-50-5)</b> |   |
| Persistence and degradability                       | Readily biodegradable in water. Not established.  |
| <b>Butyl Triglycoether (143-22-6)</b>               |   |
| Persistence and degradability                       | Readily biodegradable in water. Low potential for adsorption in soil. Photooxidation in the air. Not established. |

# PETRA SYNTHETIC DOT 4 BRAKE FLUID

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

|   |   |
|---|---|
| <b>Polyethylene Glycol (25322-68-3)</b>                                 |   |
| Persistence and degradability   | Readily biodegradable in water. Not established.  |
| <b>2-(2-Butoxyethoxy) Ethanol (112-34-5)</b>                            |   |
| Persistence and degradability   | Readily biodegradable in water. Low potential for adsorption in soil. Photooxidation in the air. Not established.         |
| <b>Diethylene Glycol (111-46-6)</b>                                     |   |
| Persistence and degradability   | Readily biodegradable in water. Biodegradable in the soil. Highly mobile in soil. Photolysis in the air. Not established. |
| Biochemical oxygen demand (BOD)   | 0.02 g O <sub>2</sub> /g substance  |
| Chemical oxygen demand (COD)  | 1.51 g O <sub>2</sub> /g substance  |
| ThOD  | 1.51 g O <sub>2</sub> /g substance  |
| BOD (% of ThOD)   | 0.015   |
| <b>Diethyleneglycolmonoethyl Ether (111-90-0)</b>                       |   |
| Persistence and degradability   | Readily biodegradable in water. Not established.  |
| Biochemical oxygen demand (BOD)   | 0.2 g O <sub>2</sub> /g substance   |
| Chemical oxygen demand (COD)  | 1.85 g O <sub>2</sub> /g substance  |
| ThOD  | 1.9078849 g O <sub>2</sub> /g substance   |
| BOD (% of ThOD)   | 0.11  |
| <b>Triethyleneglycol (112-27-6)</b>                                     |   |
| Persistence and degradability   | Inherently biodegradable. Readily biodegradable in water. Photolysis in the air. Not established.                         |
| Biochemical oxygen demand (BOD)   | 0.03 g O <sub>2</sub> /g substance  |
| Chemical oxygen demand (COD)  | 1.57 g O <sub>2</sub> /g substance  |
| ThOD  | 1.6 g O <sub>2</sub> /g substance   |
| <b>Methoxypolyethyleneglycols (9004-74-4)</b>                           |   |
| Persistence and degradability   | Biodegradability in water: no data available. Not established.  |
| <b>Poly(oxy-1,2-ethanediyl), alpha-butyl-omega-hydroxy- (9004-77-7)</b> |   |
| Persistence and degradability   | Readily biodegradable in water. Not established.  |
| <b>Triethylene Glycol Monomethyl Ether (112-35-6)</b>                   |   |
| Persistence and degradability   | Inherently biodegradable. Non degradable in the soil. Photodegradation in the air. Not established.                       |
| <b>Diisopropanolamine (110-97-4)</b>                                    |   |
| Persistence and degradability   | Not readily biodegradable in water. Not established.  |
| <b>Diethanolamine (111-42-2)</b>  |   |
| Persistence and degradability   | Readily biodegradable in water. Biodegradable in the soil. Photodegradation in the air.                                   |
| Biochemical oxygen demand (BOD)   | 0.22 g O <sub>2</sub> /g substance  |
| Chemical oxygen demand (COD)  | 1.52 g O <sub>2</sub> /g substance  |
| ThOD  | 2.13 g O <sub>2</sub> /g substance  |
| BOD (% of ThOD)   | 0.1   |
| <b>12.3. Bioaccumulative potential</b>                                  |   |
| <b>PETRA SYNTHETIC DOT 4 BRAKE FLUID 12 FL.OZ.</b>                      |   |
| Bioaccumulative potential   | Not established.  |
| <b>Triethyleneglycol Monoethyl Ether (112-50-5)</b>                     |   |
| Bioaccumulative potential   | Not bioaccumulative. Not established.   |
| <b>Butyl Triglycoether (143-22-6)</b>                                   |   |
| Log Pow   | 0.51 (20 °C)  |
| Bioaccumulative potential   | Low potential for bioaccumulation (Log Kow < 4). Not established.   |
| <b>Polyethylene Glycol (25322-68-3)</b>                                 |   |
| BCF fish 1  | 3.2 (Other, Pisces, Calculated value)   |
| Log Pow   | -0.96 - -0.7 (Weight of evidence approach, Other, 30 °C)  |
| Bioaccumulative potential   | Not bioaccumulative. Not established.   |
| <b>2-(2-Butoxyethoxy) Ethanol (112-34-5)</b>                            |   |
| Log Pow   | 1 (Test data; Equivalent or similar to OECD 107; 20 °C)   |
| Bioaccumulative potential   | Low potential for bioaccumulation (Log Kow < 4). Not established.   |
| <b>Diethylene Glycol (111-46-6)</b>                                     |   |
| BCF fish 1  | 100 (BCF; Other; 3 days; Leuciscus melanotus; Static system; Fresh water; Experimental value)                             |



# PETRA SYNTHETIC DOT 4 BRAKE FLUID

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

|   |  |
|---|--|
| <b>Diethylene Glycol (111-46-6)</b>                                     |  |
| Log Pow   | -1.98 (Calculated; Other)  |
| Bioaccumulative potential   | Low potential for bioaccumulation (BCF < 500). Not established.                                |
| <b>Diethyleneglycolmonoethyl Ether (111-90-0)</b>                       |  |
| Log Pow   | -1.19 - -0.08  |
| Bioaccumulative potential   | Bioaccumulation: not applicable. Not established.  |
| <b>Triethyleneglycol (112-27-6)</b>                                     |  |
| Log Pow   | -2.08 - -1.17 (Calculated)   |
| Bioaccumulative potential   | Low potential for bioaccumulation (Log Kow < 4). Not established.                              |
| <b>Methoxypolyethyleneglycols (9004-74-4)</b>                           |  |
| Bioaccumulative potential   | No bioaccumulation data available. Not established.  |
| <b>Poly(oxy-1,2-ethanediyl), alpha-butyl-omega-hydroxy- (9004-77-7)</b> |  |
| Log Pow   | 0.436 (Experimental value, EU Method A.8: Partition Coefficient, 25.5 °C)                      |
| Bioaccumulative potential   | Low potential for bioaccumulation (Log Kow < 4). Not established.                              |
| <b>Triethylene Glycol Monomethyl Ether (112-35-6)</b>                   |  |
| Log Pow   | -1.13  |
| Bioaccumulative potential   | Bioaccumulation: not applicable. Not established.  |
| <b>Diisopropanolamine (110-97-4)</b>                                    |  |
| Log Pow   | -0.79  |
| Bioaccumulative potential   | Bioaccumulation: not applicable. Not established.  |
| <b>Diethanolamine (111-42-2)</b>  |  |
| Log Pow   | -2.18 - -1.43 (Experimental value)   |
| Bioaccumulative potential   | Bioaccumulation: not applicable.   |
| <b>12.4. Mobility in soil</b>   |  |
| <b>Butyl Triglycoether (143-22-6)</b>                                   |  |
| Surface tension   | 0.0614 N/m (°C)  |
| <b>Polyethylene Glycol (25322-68-3)</b>                                 |  |
| Log Koc   | 1 (log Koc, Other, Calculated value)   |
| Ecology - soil  | Highly mobile in soil.   |
| <b>2-(2-Butoxyethoxy) Ethanol (112-34-5)</b>                            |  |
| Surface tension   | 0.0069 N/m (20 °C)   |
| <b>Diethylene Glycol (111-46-6)</b>                                     |  |
| Surface tension   | 0.0485 N/m   |
| Log Koc   | Koc, SRC PCKOCWIN v1.66; 1; Calculated value; log Koc; SRC PCKOCWIN v1.66; 0; Calculated value |
| <b>Diethyleneglycolmonoethyl Ether (111-90-0)</b>                       |  |
| Surface tension   | 0.032 N/m (25 °C)  |
| <b>Triethyleneglycol (112-27-6)</b>                                     |  |
| Surface tension   | 0.045 N/m (20 °C)  |
| <b>Poly(oxy-1,2-ethanediyl), alpha-butyl-omega-hydroxy- (9004-77-7)</b> |  |
| Surface tension   | 0.0614 N/m (20 °C)   |
| Ecology - soil  | Low potential for adsorption in soil.  |
| <b>Triethylene Glycol Monomethyl Ether (112-35-6)</b>                   |  |
| Surface tension   | 0.0314 N/m   |

### 12.5. Other adverse effects

Other information : Avoid release to the environment.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Product/Packaging disposal recommendations : Dispose in a safe manner in accordance with local/national regulations. Dispose of contents/container to appropriate waste disposal facility, in accordance with local, regional, national, international regulations.

Ecology - waste materials : Avoid release to the environment.



# PETRA SYNTHETIC DOT 4 BRAKE FLUID

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

US DOT (ground): Not regulated,  
ICAO/IATA (air): Not regulated,  
IMO/IMDG (water): Not regulated,

#### 14.2. UN proper shipping name

Proper Shipping Name (DOT) : Not regulated

#### 14.3. Additional information

Other information : No supplementary information available.

#### Overland transport

No additional information available

#### Transport by sea

No additional information available

#### Air transport

No additional information available

### SECTION 15: Regulatory information

#### 15.1. US Federal regulations

**PETRA SYNTHETIC DOT 4 BRAKE FLUID 12 FL.OZ.**

Listed on the United States TSCA (Toxic Substances Control Act) inventory

|                                     |  |
|-------------------------------------|--|
| SARA Section 311/312 Hazard Classes | Immediate (acute) health hazard<br>Delayed (chronic) health hazard |
|-------------------------------------|--|

**Triethyleneglycol Monoethyl Ether (112-50-5)**

Subject to reporting requirements of United States SARA Section 313

**Triethylene Glycol Monomethyl Ether (112-35-6)**

Subject to reporting requirements of United States SARA Section 313

#### 15.2. International regulations

##### CANADA

**PETRA SYNTHETIC DOT 4 BRAKE FLUID 12 FL.OZ.**

Listed on the Canadian DSL (Domestic Substances List)

**Triethylene Glycol Monomethyl Ether (112-35-6)**

#### EU-Regulations

**Triethylene Glycol Monomethyl Ether (112-35-6)**

#### Classification according to Regulation (EC) No. 1272/2008 [CLP]

#### Classification according to Directive 67/548/EEC [DSD] or 1999/45/EC [DPD]

Xi; R41  
Xi; R38  
R52/53

Full text of R-phrases: see section 16

##### 15.2.2. National regulations

**PETRA SYNTHETIC DOT 4 BRAKE FLUID 12 FL.OZ.**

Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)

**Triethylene Glycol Monomethyl Ether (112-35-6)**

#### 15.3. US State regulations

**PETRA SYNTHETIC DOT 4 BRAKE FLUID 12 FL.OZ.**

|   |    |
|---|----|
| U.S. - California - Proposition 65 - Carcinogens List               | No |
| U.S. - California - Proposition 65 - Developmental Toxicity         | No |
| U.S. - California - Proposition 65 - Reproductive Toxicity - Female | No |

# PETRA SYNTHETIC DOT 4 BRAKE FLUID

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

| PETRA SYNTHETIC DOT 4 BRAKE FLUID 12 FL.OZ.                       |   |  |   |                                   |
|---|---|--|---|-----------------------------------|
| U.S. - California - Proposition 65 - Reproductive Toxicity - Male |   | No   |   |                                   |
| State or local regulations  |   | U.S. - Pennsylvania - RTK (Right to Know) List<br>U.S. - New Jersey - Right to Know Hazardous Substance List |   |                                   |
| Triethyleneglycol Monoethyl Ether (112-50-5)                      |   |  |   |                                   |
| U.S. - California - Proposition 65 - Carcinogens List             | U.S. - California - Proposition 65 - Developmental Toxicity | U.S. - California - Proposition 65 - Reproductive Toxicity - Female  | U.S. - California - Proposition 65 - Reproductive Toxicity - Male | Non-significant risk level (NSRL) |
| No  | No  | No   | No  |                                   |
| Butyl Triglycolether (143-22-6)                                   |   |  |   |                                   |
| U.S. - California - Proposition 65 - Carcinogens List             | U.S. - California - Proposition 65 - Developmental Toxicity | U.S. - California - Proposition 65 - Reproductive Toxicity - Female  | U.S. - California - Proposition 65 - Reproductive Toxicity - Male | Non-significant risk level (NSRL) |
| No  | No  | No   | No  |                                   |
| Polyethylene Glycol (25322-68-3)                                  |   |  |   |                                   |
| U.S. - California - Proposition 65 - Carcinogens List             | U.S. - California - Proposition 65 - Developmental Toxicity | U.S. - California - Proposition 65 - Reproductive Toxicity - Female  | U.S. - California - Proposition 65 - Reproductive Toxicity - Male | Non-significant risk level (NSRL) |
| No  | No  | No   | No  |                                   |
| 2-(2-Butoxyethoxy) Ethanol (112-34-5)                             |   |  |   |                                   |
| U.S. - California - Proposition 65 - Carcinogens List             | U.S. - California - Proposition 65 - Developmental Toxicity | U.S. - California - Proposition 65 - Reproductive Toxicity - Female  | U.S. - California - Proposition 65 - Reproductive Toxicity - Male | Non-significant risk level (NSRL) |
| No  | No  | No   | No  |                                   |
| Diethylene Glycol (111-46-6)                                      |   |  |   |                                   |
| U.S. - California - Proposition 65 - Carcinogens List             | U.S. - California - Proposition 65 - Developmental Toxicity | U.S. - California - Proposition 65 - Reproductive Toxicity - Female  | U.S. - California - Proposition 65 - Reproductive Toxicity - Male | Non-significant risk level (NSRL) |
| No  | No  | No   | No  |                                   |
| Diethyleneglycolmonoethyl Ether (111-90-0)                        |   |  |   |                                   |
| U.S. - California - Proposition 65 - Carcinogens List             | U.S. - California - Proposition 65 - Developmental Toxicity | U.S. - California - Proposition 65 - Reproductive Toxicity - Female  | U.S. - California - Proposition 65 - Reproductive Toxicity - Male | Non-significant risk level (NSRL) |
| No  | No  | No   | No  |                                   |
| Triethyleneglycol (112-27-6)                                      |   |  |   |                                   |
| U.S. - California - Proposition 65 - Carcinogens List             | U.S. - California - Proposition 65 - Developmental Toxicity | U.S. - California - Proposition 65 - Reproductive Toxicity - Female  | U.S. - California - Proposition 65 - Reproductive Toxicity - Male | Non-significant risk level (NSRL) |
| No  | No  | No   | No  |                                   |
| Methoxypolyethyleneglycols (9004-74-4)                            |   |  |   |                                   |
| U.S. - California - Proposition 65 - Carcinogens List             | U.S. - California - Proposition 65 - Developmental Toxicity | U.S. - California - Proposition 65 - Reproductive Toxicity - Female  | U.S. - California - Proposition 65 - Reproductive Toxicity - Male | Non-significant risk level (NSRL) |
| No  | No  | No   | No  |                                   |
| Poly(oxy-1,2-ethanediyl), alpha-butyl-omega-hydroxy- (9004-77-7)  |   |  |   |                                   |
| U.S. - California - Proposition 65 - Carcinogens List             | U.S. - California - Proposition 65 - Developmental Toxicity | U.S. - California - Proposition 65 - Reproductive Toxicity - Female  | U.S. - California - Proposition 65 - Reproductive Toxicity - Male | Non-significant risk level (NSRL) |
| No  | No  | No   | No  |                                   |

# PETRA SYNTHETIC DOT 4 BRAKE FLUID

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

| Triethylene Glycol Monomethyl Ether (112-35-6)  |   |   |   |                                   |
|---|---|---|---|-----------------------------------|
| U.S. - California - Proposition 65 - Carcinogens List   | U.S. - California - Proposition 65 - Developmental Toxicity | U.S. - California - Proposition 65 - Reproductive Toxicity - Female | U.S. - California - Proposition 65 - Reproductive Toxicity - Male | Non-significant risk level (NSRL) |
| No  | No  | No  | No  |                                   |
| Diisopropanolamine (110-97-4)   |   |   |   |                                   |
| U.S. - California - Proposition 65 - Carcinogens List   | U.S. - California - Proposition 65 - Developmental Toxicity | U.S. - California - Proposition 65 - Reproductive Toxicity - Female | U.S. - California - Proposition 65 - Reproductive Toxicity - Male | Non-significant risk level (NSRL) |
| No  | No  | No  | No  |                                   |
| Diethanolamine (111-42-2)   |   |   |   |                                   |
| U.S. - California - Proposition 65 - Carcinogens List   | U.S. - California - Proposition 65 - Developmental Toxicity | U.S. - California - Proposition 65 - Reproductive Toxicity - Female | U.S. - California - Proposition 65 - Reproductive Toxicity - Male | Non-significant risk level (NSRL) |
| Yes   | No  | No  | No  |                                   |
| Triethyleneglycol Monoethyl Ether (112-50-5)  |   |   |   |                                   |
| State or local regulations  |   |   |   |                                   |
| U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List<br>U.S. - New Jersey - Right to Know Hazardous Substance List |   |   |   |                                   |
| Triethyleneglycol (112-27-6)  |   |   |   |                                   |
| State or local regulations  |   |   |   |                                   |
| U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List   |   |   |   |                                   |
| Triethylene Glycol Monomethyl Ether (112-35-6)  |   |   |   |                                   |
| State or local regulations  |   |   |   |                                   |
| U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List<br>U.S. - New Jersey - Right to Know Hazardous Substance List |   |   |   |                                   |
| Diethanolamine (111-42-2)   |   |   |   |                                   |
| State or local regulations  |   |   |   |                                   |
| U.S. - California - Proposition 65  |   |   |   |                                   |

## SECTION 16: Other information

Indication of changes : Revision - See : \*

Other information : None.

Full text of H-phrases:

|      |   |
|------|---|
| H302 | Harmful if swallowed  |
| H315 | Causes skin irritation  |
| H318 | Causes serious eye damage   |
| H319 | Causes serious eye irritation                                     |
| H373 | May cause damage to organs through prolonged or repeated exposure |

NFPA health hazard


: 2 - Intense or continued exposure could cause temporary incapacitation or possible residual injury unless prompt medical attention is given.

NFPA fire hazard

: 1 - Must be preheated before ignition can occur.

NFPA reactivity

: 0 - Normally stable, even under fire exposure conditions, and are not reactive with water.



## HMIS III Rating

Health : 2 Moderate Hazard - Temporary or minor injury may occur

Flammability : 1 Slight Hazard

Physical : 0 Minimal Hazard

Personal Protection : B

# PETRA SYNTHETIC DOT 4 BRAKE FLUID

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

---

SDS US (GHS HazCom 2012) - TCC

*The Supplier identified in Section 1 of this SDS has evaluated this product and certifies it to be labeled and packaged in compliance with the applicable provisions of the Federal Hazardous Substance Act as stated in 16 CFR 1500 and enforced by the Consumer Product Safety Commission, and where applicable the products that require Child Resistant Closures are packaged in accordance with the Poison Prevention Packaging Act as stated in 16 CFR 1700 and enforced by the Consumer Product Safety Commission. All closures have been tested in accordance with the latest protocols. No other testing is required to certify compliance with the above. The date of manufacture is stamped on the product*

*Disclaimer: The information and recommendations contained herein are based upon tests believed to be reliable. However, the manufacturer/distributor of this product does not guarantee their accuracy or completeness NOR SHALL ANY OF THIS INFORMATION CONSTITUTE A WARRANTY, WHETHER EXPRESSED OR IMPLIED, AS TO THE SAFETY OF THE GOODS, THE MERCHANTABILITY OF THE GOODS, OR THE FITNESS OF THE GOODS FOR A PARTICULAR PURPOSE. Adjustment to conform to actual conditions of usage may be required. The manufacturer/distributor assumes no responsibility for results obtained or for incidental or consequential damages, including lost profits, arising from the use of these data. No warranty against infringement of any patent, copyright or trademark is made or implied.*