

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Version: 1.2

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture

Trade name : PETRA GLASS CLEANER

Product code : 9005G55

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Glass Cleaner

1.3. Details of the supplier of the safety data sheet

Petra Oil Company 11085 Regency Green Drive Cypress, TX 77429 T 713-856-5700

1.4. Emergency telephone number

Emergency number : CHEMTREC 24 Hour 1-800-424-9300, 1-703-527-3887 (International)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GHS-US classification

Compressed gas H280 STOT SE 1 H370

Full text of H statements : see section 16

2.2. Label elements

GHS-US labeling

Hazard pictograms (GHS-US)





604 GHS08

Signal word (GHS-US) : Danger

Hazard statements (GHS-US) : H280 - Contains gas under pressure; may explode if heated

H370 - Causes damage to organs

Precautionary statements (GHS-US) : P260 - Do not breathe dust,fumes,gas,mist,vapor spray

P264 - Wash affected areas thoroughly after handling P270 - Do not eat, drink or smoke when using this product P307+P311 - If exposed: Call a poison center/doctor P321 - Specific treatment: See section 4.1 on SDS

P405 - Store locked up

P410+P403 - Protect from sunlight. Store in a well-ventilated place

P501 - Dispose of contents/container to appropriate waste disposal facility, in accordance with

local, regional, national, international regulations.

2.3. Other hazards

Other hazards not contributing to the classification

: Contains gas under pressure; may explode if heated. None under normal conditions.

2.4. Unknown acute toxicity (GHS US)

No data available

SECTION 3: Composition/Information on ingredients

3.1. Substance

Not applicable

3.2. Mixture

Name	Product identifier	%	GHS-US classification
Water	(CAS No) 7732-18-5	85 - 95	Not classified
Methanol	(CAS No) 67-56-1	1 - 5	Flam. Liq. 2, H225 Acute Tox. 3 (Oral), H301 Acute Tox. 3 (Dermal), H311 Acute Tox. 3 (Inhalation:dust,mist), H331 STOT SE 1, H370

EN (English US) 1/12

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Name	Product identifier	%	GHS-US classification
Petroleum Gases, Liquefied, Sweetened	(CAS No) 68476-86-8	1 - 5	Flam. Gas 1, H220 Compressed gas, H280
2-Butoxyethanol	(CAS No) 111-76-2	<1	Flam. Liq. 4, H227 Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation:dust,mist), H332 Skin Irrit. 2, H315 Eye Irrit. 2A, H319
Ethanol	(CAS No) 64-17-5	0.73525 - 0.7785	Flam. Liq. 2, H225
Ammonium Hydroxide, Aqueous Solution, Conc=25%	(CAS No) 1336-21-6	< 1	Skin Corr. 1B, H314 Aquatic Acute 1, H400
2-Aminoethanol	(CAS No) 141-43-5	<= 0.05593	Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation), H332 Skin Corr. 1A, H314
2-Propanol	(CAS No) 67-63-0	0 - 0.04325	Flam. Liq. 2, H225 Eye Irrit. 2A, H319 STOT SE 3, H336
Proprietary Inhibitor Package	(CAS No) Proprietary	<= 0.01974	Not classified
Methyl Isobutyl Ketone	(CAS No) 108-10-1	0 - 0.00865	Flam. Liq. 2, H225 Acute Tox. 3 (Inhalation:gas), H331 Eye Irrit. 2A, H319 STOT SE 3, H335
Polyethylene Glycol 200-600	(CAS No) 25322-68-3	<= 0.00144	Not classified
Nonyl Nonoxynol-5	(CAS No) 9014-93-1	<= 0.00096	Not classified

The exact percentage is a trade secret.

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general : Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible). Call a POISON CENTER or doctor/physician.

First-aid measures after inhalation : Remove victim to fresh air and keep at rest in a position comfortable for breathing.

First-aid measures after skin contact : Remove affected clothing and wash all exposed skin area with mild soap and water, followed

by warm water rinse.

First-aid measures after eye contact : Remove contact lenses, if present and easy to do. Continue rinsing. Rinse cautiously with water for several minutes. Obtain medical attention if pain, blinking or redness persist.

First-aid measures after ingestion : Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries : Causes damage to organs.

Symptoms/injuries after skin contact : May cause slight irritation . May cause moderate irritation. Itching. Red skin. Skin

rash/inflammation.

Symptoms/injuries after eye contact : May cause slight irritation. May cause slight eye irritation . Inflammation/damage of the eye

tissue. Irritation of the eye tissue. Redness of the eye tissue.

Symptoms/injuries after ingestion : May be harmful if swallowed and enters airways. May be fatal if swallowed and enters airways.

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Foam. Dry powder. Carbon dioxide. Water spray. Sand.

Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

No additional information available

5.3. Advice for firefighters

Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any

chemical fire. Prevent fire-fighting water from entering environment.

Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

Other information : NFPA Aerosol Level 1.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Remove ignition sources.

EN (English US) 2/12

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

6.1.1. For non-emergency personnel

Protective equipment : Gloves. Safety glasses.

Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

Protective equipment : Equip cleanup crew with proper protection. Avoid breathing dust,fume,gas,mist,vapor spray.

Emergency procedures : Ventilate area.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

For containment : Dam up the liquid spill. Plug the leak, cut off the supply. Contain released substance, pump into

suitable containers.

Methods for cleaning up : Store away from other materials.

6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed

: Pressurized container: Do not pierce or burn, even after use.

Precautions for safe handling : Wash hands and other exposed areas with mild soap and water before eating, drinking or

smoking and when leaving work. Provide good ventilation in process area to prevent formation

of vapor. Do not breathe dust,fumes,gas,mist,vapor spray.

Hygiene measures : Do not eat, drink or smoke when using this product. Wash contaminated clothing before reuse. Separate working clothes from town clothes. Launder separately. Remove contaminated

clothes. Always wash hands after handling the product. Wash affected areas thoroughly after handling. Wash hands and other exposed areas with mild soap and water before eating,

drinking or smoking and when leaving work.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Proper grounding procedures to avoid static electricity should be followed. Comply with

applicable regulations.

Storage conditions : Keep only in the original container in a cool, well ventilated place away from : Keep container

closed when not in use.

Incompatible products : Strong bases. Strong acids.

Incompatible materials : Sources of ignition. Direct sunlight. Storage area : Store in a well-ventilated place.

7.3. Specific end use(s)

Follow Label Directions.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Petroleum Gases. Lie	quefied, Sweetened (68476-86-8)	
USA ACGIH	ACGIH TWA (ppm)	1000 ppm Listed under Aliphatic hydrocarbon gases alkane C1-C4
USA OSHA	OSHA PEL (TWA) (mg/m³)	1800 mg/m³
USA OSHA	OSHA PEL (TWA) (ppm)	1000 ppm
2-Butoxyethanol (111-76-2)		
USA ACGIH	ACGIH TWA (mg/m³)	97 mg/m³
USA ACGIH	ACGIH TWA (ppm)	20 ppm (2-Butoxyethanol (EGBE); USA; Time- weighted average exposure limit 8 h; TLV - Adopted Value)
USA OSHA	OSHA PEL (TWA) (mg/m³)	240 mg/m³
USA OSHA	OSHA PEL (TWA) (ppm)	50 ppm
Ammonium Hydroxide, Aqueous Solution, Conc=25% (1336-21-6)		
USA ACGIH	ACGIH TWA (ppm)	24 ppm
USA ACGIH	ACGIH STEL (ppm)	35 ppm
USA OSHA	OSHA PEL (TWA) (ppm)	50 ppm
2-Aminoethanol (141-43-5)		
USA ACGIH	ACGIH TWA (ppm)	3 ppm (Ethanolamine; USA; Time-weighted average

EN (English US) 3/12

exposure limit 8 h; TLV - Adopted Value)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

2-Aminoethanol (141-43-5)		
USA ACGIH	ACGIH STEL (ppm)	6 ppm (Ethanolamine; USA; Short time value; TLV - Adopted Value)
Methanol (67-56-1)		
USA ACGIH	ACGIH TWA (mg/m³)	262 mg/m³
USA ACGIH	ACGIH TWA (ppm)	200 ppm (Methanol; USA; Time-weighted average exposure limit 8 h; TLV - Adopted Value)
USA ACGIH	ACGIH STEL (mg/m³)	328 mg/m³
USA ACGIH	ACGIH STEL (ppm)	250 ppm
USA OSHA	OSHA PEL (TWA) (mg/m³)	260 mg/m³
USA OSHA	OSHA PEL (TWA) (ppm)	200 ppm
Methyl Isobutyl Ketone (108-10-1)		
USA ACGIH	ACGIH TWA (ppm)	20 ppm (Methyl isobutyl ketone; USA; Time-weighted average exposure limit 8 h; TLV - Adopted Value)
USA ACGIH	ACGIH STEL (ppm)	75 ppm (Methyl isobutyl ketone; USA; Short time

8.2. **Exposure controls**

Appropriate engineering controls : Local exhaust venilation, vent hoods . Ensure good ventilation of the work station.

Personal protective equipment : Gloves. Safety glasses. Avoid all unnecessary exposure.





value; TLV - Adopted Value)

Materials for protective clothing GIVE EXCELLENT RESISTANCE:

Hand protection Wear protective gloves.

Eye protection Chemical goggles or safety glasses. Skin and body protection Wear suitable protective clothing.

Respiratory protection Where exposure through inhalation may occur from use, respiratory protection equipment is

recommended.

Environmental exposure controls : Avoid release to the environment.

Consumer exposure controls : Avoid contact during pregnancy/while nursing.

Other information : Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

Information on basic physical and chemical properties

: Gas Physical state Appearance : Liquid.

Color : Colourless to light yellow.

: Mild . Alcohol odour. Ammonia odour. Odor

Odor threshold : No data available

рΗ : 9

Relative evaporation rate (butyl acetate=1) : No data available Melting point : No data available Freezing point : No data available

Boiling point : -31.1 °C (Lowest Component-Propellant) -96.23 °C (Lowest Component-Propellant) Flash point

Auto-ignition temperature : No data available Decomposition temperature : No data available Flammability (solid, gas) : No data available No data available Vapor pressure : No data available Relative vapor density at 20 °C

Relative density : 0.98

Solubility : Soluble in water. Log Pow No data available Log Kow : No data available Viscosity, kinematic : No data available Viscosity, dynamic : No data available

> EN (English US) 4/12

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

: No data available Explosive properties Oxidizing properties : No data available Explosion limits : No data available

9.2. Other information

VOC content : 9.8 %

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. **Chemical stability**

Not established.

10.3. Possibility of hazardous reactions

Not established.

IARC group

10.4. **Conditions to avoid**

Direct sunlight. Extremely high or low temperatures.

Incompatible materials

Strong acids. Strong bases.

Hazardous decomposition products

Toxic fume. . Carbon monoxide. Carbon dioxide.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity	: Not classified
2-Butoxyethanol (111-76-2)	
LD50 oral rat	1300 mg/kg
LD50 dermal rat	> 2000 mg/kg body weight (Rat; Experimental value; OECD 402: Acute Dermal Toxicity)
LD50 dermal rabbit	435 mg/kg (435 mg/kg bodyweight; Rabbit; Rabbit; Experimental value,435 mg/kg bodyweight; Rabbit; Rabbit; Experimental value)
LC50 inhalation rat (mg/l)	2.17 mg/l/4h (Rat; Experimental value; 2.35 mg/l/4h; Rat; Experimental value)
LC50 inhalation rat (ppm)	450-486,Rat; Weight of evidence
Polyethylene Glycol 200-600 (25322-68-3)	
LD50 oral rat	> 15000 mg/kg (Rat)
LD50 dermal rabbit	> 20000 mg/kg (Rabbit)
2-Aminoethanol (141-43-5)	
LD50 oral rat	1720 mg/kg (Rat)
LD50 dermal rabbit	1018 mg/kg (Rabbit)
Methanol (67-56-1)	
LD50 oral rat	>= 2528 mg/kg body weight application as 50% aqueous solution
LD50 dermal rabbit	17100 mg/kg corresponding to 20 ml/kg bw according to the authors
LC50 inhalation rat (mg/l)	128.2 mg/l/4h Air
Methyl Isobutyl Ketone (108-10-1)	
LD50 oral rat	2080 mg/kg (Rat; Equivalent or similar to OECD 401; Experimental value)
LD50 dermal rat	>= 2000 mg/kg body weight (Rat; Experimental value; OECD 402: Acute Dermal Toxicity)
LD50 dermal rabbit	> 16000 mg/kg (Rabbit)
LC50 inhalation rat (mg/l)	8.2- 16.4,Rat; Experimental value
LC50 inhalation rat (ppm)	2000 ppm/4h (Rat; Experimental value,Rat; Experimental value)
Skin corrosion/irritation	: Not classified
	pH: 9
Serious eye damage/irritation	: Not classified
	pH: 9
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified Based on available data, the classification criteria are not met
• •	: Not classified
2-Butoxyethanol (111-76-2)	

3

EN (English US) 5/12

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Reproductive toxicity : Not classified

Specific target organ toxicity (single exposure) : Causes damage to organs.

Specific target organ toxicity (repeated

exposure)

: Not classified

Aspiration hazard : Not classified

Potential Adverse human health effects and

Symptoms/injuries after skin contact

symptoms

: Based on available data, the classification criteria are not met.

: May cause slight irritation . May cause moderate irritation. Itching. Red skin. Skin

rash/inflammation.

Symptoms/injuries after eye contact : May cause slight irritation. May cause slight eye irritation . Inflammation/damage of the eye

tissue. Irritation of the eye tissue. Redness of the eye tissue.

: May be harmful if swallowed and enters airways. May be fatal if swallowed and enters airways. Symptoms/injuries after ingestion

SECTION 12: Ecological information

12.1. **Toxicity**

Polyethylene Glycol 200-600 (25322-68-3)		
LC50 fish 2	> 5000 mg/l (LC50; 24 h)	
Threshold limit algae 2	500 mg/l (EC0; 720 h)	
2-Aminoethanol (141-43-5)		
LC50 fish 1	150 mg/l (LC50; 96 h; Salmo gairdneri)	
EC50 Daphnia 1	140 mg/l (EC50; 24 h)	
Threshold limit algae 2	35 mg/l (EC50; 72 h)	
Methanol (67-56-1)		
LC50 fish 1	15400 mg/l (LC50; EPA 660/3 - 75/009; 96 h; Lepomis macrochirus; Flow-through system; Fresh water; Experimental value)	
EC50 Daphnia 1	> 10000 mg/l (EC50; DIN 38412-11; 48 h; Daphnia magna; Static system; Fresh water; Experimental value)	
LC50 fish 2	10800 mg/l (LC50; 96 h; Salmo gairdneri)	

12.2. Persistence and degradability

Persistence and degradability Not established.

Persistence and degradability Not established

i et sistence and degradability inot established.	
2-Butoxyethanol (111-76-2)	
Persistence and degradability	Readily biodegradable in water. Biodegradable in the soil. Photodegradation in the air.
Biochemical oxygen demand (BOD)	0.71 g O ₂ /g substance
Chemical oxygen demand (COD)	2.20 g O ₂ /g substance
ThOD	2.305 g O ₂ /g substance
BOD (% of ThOD)	0.31

Ammonium Hydroxide, Aqueous Solution, Conc=25% (1336-21-6)

Persistence and degradability Readily biodegradable in water. Biodegradable in the soil. No (test)data on mobility of the components available. Ozonation in the air.

Polyethylene Glycol 200-600 (25322-68-3)

Persistence and degradability Biodegradability in water: no data available. Not established.

Nonyl Nonoxynol-5 (9014-93-1)

Persistence and degradability Not established.

2-Aminoethanol (141-43-5)

Persistence and degradability Readily biodegradable in water. Biodegradable in the soil. Biochemical oxygen demand (BOD) 0.80 g O₂ /g substance Chemical oxygen demand (COD) 1.34 g O₂ /g substance 2.49 g O₂ /g substance ThOD BOD (% of ThOD) 0.32

Proprietary Inhibitor Package (Proprietary)

Persistence and degradability Not established.

ů ,		
Methanol (67-56-1)		
	Persistence and degradability	Readily biodegradable in water. Biodegradable in the soil. Highly mobile in soil.
	Biochemical oxygen demand (BOD)	0.6 - 1.12 g O ₂ /g substance
	Chemical oxygen demand (COD)	1.42 g O ₂ /g substance

EN (English US) 6/12

Safety Data Sheet according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Party	,
Methanol (67-56-1)	4.5 a.O. /a substance
ThOD ROD (% of ThOD)	1.5 g O ₂ /g substance 0.8 (Literature study)
BOD (% of ThOD)	0.8 (Literature study)
Water (7732-18-5)	Alexander I
Persistence and degradability	Not established.
Methyl Isobutyl Ketone (108-10-1)	
Persistence and degradability	Readily biodegradable in water. Biodegradable in the soil. Biodegradable in the soil under anaerobic conditions. Low potential for adsorption in soil. Photolysis in the air. Not established.
Biochemical oxygen demand (BOD)	2.06 g O ₂ /g substance
Chemical oxygen demand (COD)	2.16 g O ₂ /g substance
ThOD	2.72 g O ₂ /g substance
BOD (% of ThOD)	0.76
12.3. Bioaccumulative potential	
PETRA GLASS CLEANER 19 OZ.	
Bioaccumulative potential	Not established.
Petroleum Gases, Liquefied, Sweetened (6847	(6-86-8)
Bioaccumulative potential	Not established.
2-Butoxyethanol (111-76-2)	
Log Pow	0.81 (Experimental value; BASF test; 25 °C)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).
Ammonium Hydroxide, Aqueous Solution, Co	nc=25% (1336-21-6)
Bioaccumulative potential	Not bioaccumulative.
Polyethylene Glycol 200-600 (25322-68-3)	
Log Pow	-1.2
Bioaccumulative potential	Bioaccumulation: not applicable. Not established.
Nonyl Nonoxynol-5 (9014-93-1)	
Bioaccumulative potential	Not established.
2-Aminoethanol (141-43-5)	
Log Pow	-1.91
Bioaccumulative potential	Bioaccumulation: not applicable.
Proprietary Inhibitor Package (Proprietary)	
Bioaccumulative potential	Not established.
Methanol (67-56-1)	
BCF fish 1	< 10 (BCF; 72 h; Leuciscus idus)
Log Pow	-0.77 (Experimental value; Other)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).
Water (7732-18-5)	
Bioaccumulative potential	Not established.
Methyl Isobutyl Ketone (108-10-1)	
BCF fish 1	2 - 5 (BCF)
Log Pow	1.9 (Experimental value; OECD 117: Partition Coefficient (n-octanol/water), HPLC method)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500). Not established.
12.4. Mobility in soil	,
<u> </u>	
2-Butoxyethanol (111-76-2) Surface tension	0.027 N/m (25 °C)
	· · · · · · · · · · · · · · · · ·
2-Aminoethanol (141-43-5) Surface tension	0.050 N/m
	0.000 (9/11)
Methanol (67-56-1)	0.033 N/m (30 °C)
Surface tension Log Koc	0.023 N/m (20 °C) Koc,PCKOCWIN v1.66; 1; Calculated value
LOG NOC	NOC, CNOOVIN VI.UU, I, Calculated value
BB (I I I I I I I I I I I I I I I I I I	
Methyl Isobutyl Ketone (108-10-1)	0.034 N/m (20.9C)
Surface tension	0.024 N/m (20 °C) Kos 101 85: Weight of ovidence: Calculated value: log Kos: 2 008: Weight of ovidence:
	0.024 N/m (20 °C) Koc,101.85; Weight of evidence; Calculated value; log Koc; 2.008; Weight of evidence; Calculated value

EN (English US) 7/12

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

12.5. Other adverse effects

Other information : Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste disposal recommendations : Container under pressure. Do not drill or burn even after use. Dispose in a safe manner in

accordance with local/national regulations. Dispose of contents/container to appropriate waste disposal facility, in accordance with local, regional, national, international regulations.

Ecology - waste materials : Avoid release to the environment.

SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

US DOT (ground): UN1950, Aerosols, 2.2, Limited Quantity ICAO/IATA (air): UN1950, Aerosols, 2.2, Limited Quantity IMO/IMDG (water): UN1950, Aerosols, 2.2, Limited Quantity

14.2. UN proper shipping name

Proper Shipping Name (DOT) : Aerosols

Non-flammable, (each not exceeding 1 L capacity)

Class (DOT) : 2.2 - Class 2.2 - Non-flammable compressed gas 49 CFR 173.115

Hazard labels (DOT) : 2.2 - Non-flammable gas



DOT Packaging Exceptions (49 CFR 173.xxx) : 306
DOT Packaging Non Bulk (49 CFR 173.xxx) : None
DOT Packaging Bulk (49 CFR 173.xxx) : None

14.3. Additional information

Other information : No supplementary information available.

Overland transport

No additional information available

Transport by sea

DOT Vessel Stowage Location : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a

passenger vessel

DOT Vessel Stowage Other : 48 - Stow "away from" sources of heat,87 - Stow "separated from" Class 1 (explosives) except

Division 14,126 - Segregation same as for Class 9, miscellaneous hazardous materials

Air transport

DOT Quantity Limitations Passenger aircraft/rail : 75 kg

(49 CFR 173.27)

DOT Quantity Limitations Cargo aircraft only (49 : 150 kg

CFR 175.75)

SECTION 15: Regulatory information

15.1. US Federal regulations

PETRA GLASS CLEANER 19 OZ.	
SARA Section 311/312 Hazard Classes	Delayed (chronic) health hazard Immediate (acute) health hazard
	Sudden release of pressure hazard

Petroleum Gases, Liquefied, Sweetened (68476-86-8)

etroleum dases, Elqueneu, dweeteneu (00470-00-0)	
SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard
	Fire hazard
	Sudden release of pressure hazard

2-Butoxyethanol (111-76-2)

Listed on the United States TSCA (Toxic Substances Control Act) inventory Subject to reporting requirements of United States SARA Section 313

EN (English US) 8/12

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

2-Butoxyethanol (111-76-2)		
SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard Delayed (chronic) health hazard Fire hazard	
2-Aminoethanol (141-43-5)		
SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard	
Methanol (67-56-1)		
Subject to reporting requirements of United State Listed on the United States TSCA (Toxic Substa Listed on the United States SARA Section 302 Listed on the United States SARA Section 355		
SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard Delayed (chronic) health hazard Fire hazard	

15.2. International regulations

CANADA

PETRA GLASS CLEANER 19 OZ.		
WHMIS Classification	Class A - Compressed Gas	
2-Butoxyethanol (111-76-2)		
Listed on the Canadian DSL (Domestic Substance	sted on the Canadian DSL (Domestic Substances List)	
Methanol (67-56-1)		
isted on the Canadian DSL (Domestic Substances List)		
WHMIS Classification	Class B Division 2 - Flammable Liquid Class D Division 1 Subdivision B - Toxic material causing immediate and serious toxic effects Class D Division 2 Subdivision A - Very toxic material causing other toxic effects Class D Division 2 Subdivision B - Toxic material causing other toxic effects	

EU-Regulations

2-Butoxyethanol (111-76-2)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

Methanol (67-56-1)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Classification according to Directive 67/548/EEC [DSD] or 1999/45/EC [DPD]

Carc.Cat.1; R45 Muta.Cat.2; R46 F+; R12 Xn; R20/21/22 Xn; R68/20/21/22

Full text of R-phrases: see section 16

15.2.2. National regulations

2-Butoxyethanol (111-76-2)

Listed on the AICS (Australian Inventory of Chemical Substances)

Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)

Listed on the Korean ECL (Existing Chemicals List)

Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)

Methanol (67-56-1)

Listed on the Canadian IDL (Ingredient Disclosure List)

15.3. US State regulations

ETRA GLASS CLEANER 19 OZ.		
U.S California - Proposition 65 - Carcinogens List	No	
U.S California - Proposition 65 - Developmental Toxicity	No	
U.S California - Proposition 65 - Reproductive Toxicity - Female	No	
U.S California - Proposition 65 - Reproductive Toxicity - Male	No	
State or local regulations	U.S California - Proposition 65	

EN (English US) 9/12

Safety Data Sheet according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Potroloum Gasos Liquot	ind Sweetenad (69476-96-9)	·		
	ried, Sweetened (68476-86-8)	II.C. California	II.C. Colifornia	Non significant rials layed
U.S California -	U.S California -	U.S California -	U.S California -	Non-significant risk level
Proposition 65 -	Proposition 65 -	Proposition 65 -	Proposition 65 -	(NSRL)
Carcinogens List	Developmental Toxicity	Reproductive Toxicity -	Reproductive Toxicity -	
		Female	Male	
No	No	No	No	
2-Butoxyethanol (111-76	-2)			
U.S California -	U.S California -	U.S California -	U.S California -	Non-significant risk level
Proposition 65 -	Proposition 65 -	Proposition 65 -	Proposition 65 -	(NSRL)
		Reproductive Toxicity -		(NSKL)
Carcinogens List	Developmental Toxicity	Female	Reproductive Toxicity - Male	
No	No	No	No	
	Aqueous Solution, Conc=25%	(1336-21-6)		
U.S California -	U.S California -	U.S California -	U.S California -	Non-significant risk level
Proposition 65 -	Proposition 65 -	Proposition 65 -	Proposition 65 -	(NSRL)
Carcinogens List	Developmental Toxicity	Reproductive Toxicity -	Reproductive Toxicity -	
_ 		Female	Male	
No	No	No	No	
Polyethylene Glycol 200-	.600 (25322-68-3)			
U.S California -	U.S California -	U.S California -	U.S California -	Non-significant risk level
Proposition 65 -	Proposition 65 -	Proposition 65 -	Proposition 65 -	(NSRL)
				(NSKL)
Carcinogens List	Developmental Toxicity	Reproductive Toxicity - Female	Reproductive Toxicity - Male	
		remaie	Male	
No	No	No	No	
Nonyl Nonoxynol-5 (9014	1-93-1)			
U.S California -	U.S California -	U.S California -	U.S California -	Non-significant risk level
Proposition 65 -	Proposition 65 -	Proposition 65 -	Proposition 65 -	(NSRL)
Carcinogens List	Developmental Toxicity	Reproductive Toxicity -	Reproductive Toxicity -	(**************************************
Carolinogorio Liot	Bovolopinional volucity	Female	Male	
No	No	No	No	
2-Aminoethanol (141-43-				
U.S California -	U.S California -	U.S California -	U.S California -	Non-significant risk level
Proposition 65 -	Proposition 65 -	Proposition 65 -	Proposition 65 -	(NSRL)
Carcinogens List	Developmental Toxicity	Reproductive Toxicity -	Reproductive Toxicity -	
		Female	Male	
No	No	No	No	
Proprietory Inhibitor Poo	kaga (Branziatary)			
Proprietary Inhibitor Pac U.S California -		U.S California -	U.S California -	Non significant riple level
				Non-significant risk level
Proposition 65 -	Proposition 65 -	Proposition 65 -	Proposition 65 -	(NSRL)
Carcinogens List	Developmental Toxicity	Reproductive Toxicity -	Reproductive Toxicity -	
		Female	Male	
No	No	No	No	
Methanol (67-56-1)				
U.S California -	U.S California -	U.S California -	U.S California -	Non-significant risk level
Proposition 65 -	Proposition 65 -	Proposition 65 -	Proposition 65 -	(NSRL)
Carcinogens List	Developmental Toxicity	Reproductive Toxicity -	Reproductive Toxicity -	(110112)
Caroniogorio Liot	Dovolopinonia Toxiony	Female	Male	
Na	Van			
No	Yes	No	No	
Water (7732-18-5)	1.1.2. 2.111	1	1	1
U.S California -	U.S California -	U.S California -	U.S California -	Non-significant risk level
Proposition 65 -	Proposition 65 -	Proposition 65 -	Proposition 65 -	(NSRL)
Carcinogens List	Developmental Toxicity	Reproductive Toxicity -	Reproductive Toxicity -	
		Female	Male	
No	No	No	No	
Mathyl Isohutul Katana (108-10-1)		<u> </u>	<u> </u>
Methyl Isobutyl Ketone (U.S California -	U.S California -	U.S California -	U.S California -	Non-significant risk level
Proposition 65 -	Proposition 65 -	Proposition 65 -	Proposition 65 -	(NSRL)
				(NOINL)
Carcinogens List	Developmental Toxicity	Reproductive Toxicity -	Reproductive Toxicity -	
		Female	Male	
Yes	No	No	No	
i	1	1	Ì	1

EN (English US) 10/12

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Petroleum Gases, Liquefied, Sweetened (68476-86-8)

State or local regulations

New Jersey Right-to-Know Minnesota Right-to-Know Rhode Island Right to Know

U.S. - Pennsylvania - RTK (Right to Know) List

U.S. - Massachusetts - Right To Know List

2-Butoxyethanol (111-76-2)

State or local regulations

U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List

U.S. - New Jersey - Right to Know Hazardous Substance List

Methanol (67-56-1)

State or local regulations

U.S. - California - Proposition 65 New Jersey Right-to-Know Florida Right to Know

U.S. - Massachusetts - Right To Know List U.S. - Pennsylvania - RTK (Right to Know) List

C.G. -1 Chinayivania - ICTIC (raight to ranow

Methyl Isobutyl Ketone (108-10-1)

State or local regulations

U.S. - California - Proposition 65

SECTION 16: Other information

Indication of changes : Revision - See : *.

Other information : None.

Full text of H-phrases:

74 O P	
H220	Extremely flammable gas
H225	Highly flammable liquid and vapor
H227	Combustible liquid
H280	Contains gas under pressure; may explode if heated
H301	Toxic if swallowed
H302	Harmful if swallowed
H311	Toxic in contact with skin
H312	Harmful in contact with skin
H314	Causes severe skin burns and eye damage
H315	Causes skin irritation
H319	Causes serious eye irritation
H331	Toxic if inhaled
H332	Harmful if inhaled
H335	May cause respiratory irritation
H336	May cause drowsiness or dizziness
H370	Causes damage to organs
H400	Very toxic to aquatic life


NFPA health hazard : 1 - Exposure could cause irritation but only minor residual

injury even if no treatment is given.

NFPA fire hazard : 1 - Must be preheated before ignition can occur.

NFPA reactivity : 0 - Normally stable, even under fire exposure conditions,

and are not reactive with water.



HMIS III Rating

Health : 1 Slight Hazard - Irritation or minor reversible injury possible

Flammability : 1 Slight Hazard Physical : 1 Slight Hazard

Personal Protection : B

SDS US (GHS HazCom 2012) - TCC

EN (English US) 11/12

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

The Supplier identified in Section 1 of this SDS has evaluated this product and certifies it to be labeled and packaged in compliance with the applicable provisions of the Federal Hazardous Substance Act as stated in 16 CFR 1500 and enforced by the Consumer Product Safety Commission, and where applicable the products that require Child Resistant Closures are packaged in accordance with the Poison Prevention Packaging Act as stated in 16 CFR 1700 and enforced by the Consumer Product Safety Commission. All closures have been tested in accordance with the latest protocols. No other testing is required to certify compliance with the above. The date of manufacture is stamped on the product

Disclaimer: The information and recommendations contained herein are based upon tests believed to be reliable. However, the manufacturer/distributor of this product does not guarantee their accuracy or completeness NOR SHALL ANY OF THIS INFORMATION CONSTITUTE A WARRANTY, WHETHER EXPRESSED OR IMPLIED, AS TO THE SAFETY OF THE GOODS, THE MERCHANTABILITY OF THE GOODS, OR THE FITNESS OF THE GOODS FOR A PARTICULAR PURPOSE. Adjustment to conform to actual conditions of usage may be required. The manufacturer/distributor assumes no responsibility for results obtained or for incidental or consequential damages, including lost profits, arising from the use of these data. No warranty against infringement of any patent, copyright or trademark is made or implied.

EN (English US) 12/12