

Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard (HCS 2024) and the Hazardous Products Regulation (WHMIS 2015 rev 2022)

Issue date: 12/2/2025 Revision date: 12/2/2025

SECTION 1 Identification

1.1. Product identifier

Product form : Mixture

Trade name : Mopar Brake Parts Cleaner

Product code : 68621515AA Aerosol : Aerosol

1.2. Other means of identification

No additional information available

1.3. Recommended use of the chemical and restrictions on use

Use of the substance/mixture : Parts,Brake cleaners
Restrictions on use : For professional use only

1.4. Supplier's details

Petra Automotive Products, Inc. 11085 Regency Green Dr. Cypress, TX 77429 USA T (713) 856-5700 www.petraautoproducts.com

1.5. Emergency phone number

Emergency number : (Chemical Spills, Leaks, Fire, Exposure or Accident only): CHEMTREC 1-800-424-9300 (in the

US), 1-703-527-3887 (Outside the US)

SECTION 2 Hazard Identification

2.1. Classification of the substance or mixture

GHS US classification

Aerosol, Category 1	H222;H229	Extremely flammable aerosol. Pressurized container; may burst
		if heated.
Skin corrosion/irritation, Category 2	H315	Causes skin irritation.
Serious eye damage/eye irritation, Category 2	H319	Causes serious eye irritation.
Reproductive toxicity, Category 2	H361	Suspected of damaging fertility or the unborn child.
Specific target organ toxicity – Single exposure, Category 3, Narcosis	H336	May cause drowsiness or dizziness.
Specific target organ toxicity — Repeated exposure, Category 2	H373	May cause damage to organs (Neurologic effect, central nervous system) through prolonged or repeated exposure (Inhalation).
Aspiration hazard, Category 1	H304	May be fatal if swallowed and enters airways.
Full text of H statements : see section 16		

2.2. Label elements

GHS US labeling

Hazard pictograms (GHS US)







Signal word (GHS US) : Danger

12/2/2025 (Revision date) US - en 1/12

Safety Data Sheet

Precautionary statements (GHS US)

According to 29CFR 1910.1200 OSHA Hazard Communication Standard (HCS 2024) and the Hazardous Products Regulation (WHMIS 2015 rev 2022)

Hazard statements (GHS US) : H222 - Extremely flammable aerosol

H229 - Pressurized container; may burst if heated H304 - May be fatal if swallowed and enters airways

H315 - Causes skin irritation

H319 - Causes serious eye irritation

H336 - May cause drowsiness or dizziness

H361 - Suspected of damaging fertility or the unborn child

H373 - May cause damage to organs (Neurologic effect, central nervous system) through

prolonged or repeated exposure (Inhalation)

: P201 - Obtain special instructions before use.

P202 - Do not handle until all safety precautions have been read and understood.

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

P211 - Do not spray on an open flame or other ignition source.

P251 - Do not pierce or burn, even after use. P260 - Do not breathe spray, vapors, mist.

P264 - Wash hands, forearms and face thoroughly after handling.

P271 - Use only outdoors or in a well-ventilated area.

P280 - Wear protective gloves, protective clothing, eye protection, face protection, and hearing protection

P301+P310 - If swallowed: Immediately call a poison center or doctor.

P331 - Do NOT induce vomiting.

P302+P352 - If on skin: Wash with plenty of water.

P332+P313 - If skin irritation occurs: Get medical advice or attention. P362+P364 - Take off contaminated clothing and wash it before reuse.

P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing.

P312 - Call a poison center or doctor if you feel unwell.

P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

P337+P313 - If eye irritation persists: Get medical advice or attention.

P308+P313 - If exposed or concerned: Get medical advice/attention.

P403 - Store in a well-ventilated place.

P405 - Store locked up.

P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 122 °F (50 °C). P501 - Dispose of contents and/or container to hazardous or special waste collection point, in

accordance with local, regional, national and/or international regulations.

2.3. Hazards associated with known or reasonably anticipated uses

None known

2.4. Hazards not otherwise classified

Other hazards which do not result in classification : Very toxic to aquatic life with long lasting effects.

2.5. Unknown acute toxicity

No additional information available

SECTION 3 Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%
Acetone	CAS-No.: 67-64-1	60-80

Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard (HCS 2024) and the Hazardous Products Regulation (WHMIS 2015 rev 2022)

Name	Product identifier	%
Heptane, branched, cyclic and linear	CAS-No.: 426260-76-6	30-60
Toluene	CAS-No.: 108-88-3	15-25
Carbon dioxide (CO2)	CAS-No.: 124-38-9	5 – 10

^{*}Chemical name, CAS number and/or exact concentration have been withheld as a trade secret

Full text of hazard classes and H-statements : see section 16

SECTION 4 First aid measures

4.1. Description of necessary first-aid measures

First-aid measures general : Call a poison center or a doctor if you feel unwell.

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. Call a poison center or a doctor

if you feel unwell.

First-aid measures after skin contact : Take off contaminated clothing. Wash skin with plenty of water and soap. If skin irritation occurs:

Get medical advice/attention. Wash contaminated clothing before reuse.

First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to

do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

First-aid measures after ingestion : Aspiration hazard. Do NOT induce vomiting. Immediately call a poison center or

doctor/physician.

4.2. Most important symptoms/effects, acute and delayed

Symptoms/effects : Aspiration hazard. May be fatal if swallowed and enters airways. Causes eye irritation. Causes skin irritation. May cause drowsiness or dizziness. May cause damage to organs (Neurologic

effect, hearing sense) through prolonged or repeated exposure (inhalation). Suspected of

damaging fertility or the unborn child.

Inhalation : May cause drowsiness or dizziness. At high concentrations, the vapors can be irritating to the

respiratory system.

Skin : Causes skin irritation.

Eyes : Causes serious eye irritation.

Ingestion : Aspiration hazard. May be fatal if swallowed and enters airways. May cause gastrointestinal

irritation, nausea, vomiting and diarrhea.

Chronic symptoms : Suspected of damaging fertility or the unborn child. May cause damage to organs (Neurologic

effect, central nervous system) through prolonged or repeated exposure (Inhalation).

4.3. Indication of immediate medical attention and special treatment needed, if necessary

Other medical advice or treatment : If accidentally swallowed obtain immediate medical attention.

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Use extinguishing media appropriate for surrounding fire. Water spray. Dry powder. Foam.

Carbon dioxide. Cool down the containers exposed to heat with a water spray.

Unsuitable extinguishing media : Do not use a solid water stream as it may scatter and spread fire.

5.2. Specific hazards arising from the chemical

Fire hazard : Extremely flammable aerosol. Contents under pressure. Keep away from open flames, hot surfaces and sources of ignition. Pressurized container: may burst if heated. Vapors are heavier

than air and may travel considerable distance to an ignition source and flash back to source of

vapors.

Hazardous decomposition products in case of fire : On combustion, forms: carbon oxides (CO and CO2).

12/2/2025 (Revision date) US - en 3/12

Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard (HCS 2024) and the Hazardous Products Regulation (WHMIS 2015 rev 2022)

5.3. Special protective equipment and precautions for fire-fighters

Protection during firefighting

: Use shielding to protect from bursting cans. Do not attempt to take action without suitable protective equipment. Complete protective clothing. Self-contained breathing apparatus.

SECTION 6 Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Ventilate spillage area. No open flames, no sparks, and no smoking. Do not breathe aerosol.

Avoid contact with eyes, skin and clothing.

For non-emergency personnel

Emergency procedures : Ventilate spillage area. No open flames, no sparks, and no smoking. Avoid breathing vapors.

Avoid contact with skin and eyes. Do not breathe mist, vapors.

For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer

to section 8: "Exposure controls/personal protection".

Environmental precautions : Do not allow product to spread into the environment.

6.2. Methods and materials for containment and cleaning up

For containment : Collect spillage.

Methods for cleaning up : Leaking cans should be placed in a plastic bag or open pail until the pressure has dissipated.

Absorb with an inert material and place in an appropriate waste disposal container.

Other information : Dispose of materials or solid residues at an authorized site.

For further information refer to section 8: "Exposure controls/personal protection". For disposal of contaminated materials refer to section 13: "Disposal considerations".

SECTION 7 Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Obtain special instructions before use. Ensure adequate ventilation. Do not breathe mist,

vapours, spray. Avoid contact with eyes, skin and clothing. Use personal protective equipment as required. Pressurized container: Do not pierce or burn, even after use. Do not spray on an open flame or other ignition source. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Handle in accordance with good industrial hygiene and

safety procedures.

Hygiene measures : Wash contaminated clothing before reuse. Contaminated work clothing should not be allowed

out of the workplace. Do not eat, drink or smoke when using this product. Always wash hands

after handling the product.

7.2. Conditions for safe storage, including incompatibilities

Technical measures : U.F.C. (NFPA 30B) Level III Aerosol.

Storage conditions : Do not expose to temperatures exceeding 50 °C/ 122 °F. Protect from sunlight. Store in a well-

ventilated place. Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking. U.F.C. (NFPA 30B) Level III Aerosol.

Storage temperature : < 50 °C Specific end uses : Cleaner.

Material used in packaging/containers : Aerosol spray can.

12/2/2025 (Revision date) US - en 4/12

Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard (HCS 2024) and the Hazardous Products Regulation (WHMIS 2015 rev 2022)

SECTION 8 Exposure controls/personal protection

8.1. Control parameters

Acetone (67-64-1)			
USA - ACGIH - Occupational Exposure Limits			
Local name	Acetone		
ACGIH® TLV® TWA	250 ppm		
ACGIH® TLV® STEL	500 ppm		
Remark (ACGIH®)	TLV® Basis: URT & eye irr; CNS impair. Notations: A4 (Not classifiable as a Human Carcinogen); BEI		
Regulatory reference	ACGIH 2024		
USA - ACGIH - Biological Exposure Indices			
Local name	Acetone		
BEI (BLV)	25 mg/l Parameter: Acetone - Medium: urine - Sampling time: End of shift - Notations: Ns		
Regulatory reference	ACGIH 2024		
USA - OSHA - Occupational Exposure Limits			
Local name	Acetone		
OSHA PEL (TWA)	2400 mg/m³		
	1000 ppm		
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1		
Toluene (108-88-3)	Toluene (108-88-3)		
USA - ACGIH - Occupational Exposure Limits			
Local name	Toluene		
ACGIH® TLV® TWA	20 ppm		
Remark (ACGIH®) TLV® Basis: CNS, visual & hearing impair; female repro system eff; pregnancy loss OTO; A4 (Not classifiable as a Human Carcinogen); BEI			
Regulatory reference	ACGIH 2024		
USA - ACGIH - Biological Exposure Indices			
Local name	Toluene		
BEI (BLV)	0.3 mg/g Kreatinin Parameter: o-Cresol (with hydrolysis) - Medium: urine - Sampling time: End of shift - Notations: B 0.03 mg/l Parameter: Toluene - Medium: urine - Sampling time: End of shift 0.02 mg/l Parameter: Toluene - Medium: blood - Sampling time: Prior to last shift of workweek		
Regulatory reference ACGIH 2024			
USA - OSHA - Occupational Exposure Limits			
Local name	Toluene		
OSHA PEL (TWA)	200 ppm		
OSHA PEL (Ceiling)	300 ppm		
Acceptable maximum peak above the acceptable ceiling concentration for an 8-hr shift 500 ppm 10 mins.			

Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard (HCS 2024) and the Hazardous Products Regulation (WHMIS 2015 rev 2022)

Toluene (108-88-3)			
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-2		
Carbon dioxide (CO2) (124-38-9)			
USA - ACGIH - Occupational Exposure Limits	USA - ACGIH - Occupational Exposure Limits		
Local name	Carbon dioxide		
ACGIH® TLV® TWA	9000 mg/m³		
	5000 ppm		
ACGIH® TLV® STEL	54000 mg/m³		
	30000 ppm		
Remark (ACGIH®)	TLV® Basis: Asphyxia		
Regulatory reference	ACGIH 2025		
USA - OSHA - Occupational Exposure Limits			
Local name	Carbon dioxide		
OSHA PEL (TWA)	9000 mg/m³		
	5000 ppm		
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1		

8.2. Appropriate engineering controls

Appropriate engineering controls : Use with adequate general or local exhaust ventilation to maintain exposure levels below the

occupational exposure limits.

Environmental exposure controls : Do not allow product to spread into the environment.

8.3. Individual protection measures, such as personal protective equipment

Hand protection:

Chemically resistant protective gloves. Consult supplier for specific recommendations.

Eye protection:

Use suitable eye protection

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

No respiratory protection needed under normal use conditions. In operations where exposure limits are exceeded or exposure levels are excessive, an approved respirator should be used. Respirator selection and use should be based on contaminant type, form and concentration. Follow applicable regulations and good Industrial Hygiene practice.

Thermal hazard protection:

Not applicable.

SECTION 9 Physical and chemical properties

9.1. Basic physical and chemical properties

Physical state : Liquic

Appearance : Aerosol can. Contains: Clear, colorless liquid.

Color : Clear, colorless liquid

Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard (HCS 2024) and the Hazardous Products Regulation (WHMIS 2015 rev 2022)

Odor : Aromatic
Odor threshold : Not determined
pH : Not applicable
Melting point : Not applicable
Freezing point : No data available
Boiling point : 56.05 °C Acetone
Flash point : < -17 °C Acetone

Relative evaporation rate (butyl acetate=1) : < 1

Flammability (solid, gas) : Extremely flammable aerosol.

Vapor pressure : Not determined

Relative vapor density at 20°C : > 1

Relative density : Not determined
Density : Not determined
Solubility : Not determined.

Partition coefficient n-octanol/water (Log Pow) : No data available
Auto-ignition temperature : Not determined
Decomposition temperature : Not determined
Viscosity, kinematic : < 20 mm²/s

Explosion limits : Lower explosion limit: 1.1 vol % Toluene

Upper explosion limit: 12.8 vol % Acetone

Oxidizing properties : Not oxidising.

Particle characteristics : Particle characteristics : Not applicable

9.2. Data relevant with regard to physical hazard classes (supplemental)

No additional information available

SECTION 10 Stability and reactivity

10.1. Reactivity

Extremely flammable aerosol.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

Strong oxidizing agents. Acids. Strong bases.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11 Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified Acute toxicity (dermal) : Not classified Acute toxicity (inhalation) : Not classified

Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard (HCS 2024) and the Hazardous Products Regulation (WHMIS 2015 rev 2022)

Acetone (67-64-1)			
LD50 oral rat	5800 mg/kg		
LC50 Inhalation - Rat	76 mg/l		
Toluene (108-88-3)			
LD50 oral rat	5580 mg/kg body weight		
LD50 dermal rabbit	> 5000 mg/kg body weight		
LC50 Inhalation - Rat	28.1 mg/l/4h		
Skin corrosion/irritation :	Causes skin irritation.		
Serious eye damage/irritation :	pH: Not applicable Causes serious eye irritation. pH: Not applicable		
Respiratory or skin sensitization :	Not classified		
Germ cell mutagenicity :	Not classified		
Carcinogenicity :	Not classified		
Toluene (108-88-3)			
IARC group	3 - Not classifiable		
Reproductive toxicity :	Suspected of damaging fertility or the unborn child.		
Acetone (67-64-1)			
LOAEL (animal/female, F0/P)	11298 mg/kg body weight mouse		
NOAEL (animal/male, F0/P)	900 mg/kg body weight rat		
STOT-single exposure :	May cause drowsiness or dizziness.		
Acetone (67-64-1)			
STOT-single exposure	May cause drowsiness or dizziness.		
Heptane, branched, cyclic and linear (426260-	76-6)		
STOT-single exposure	May cause drowsiness or dizziness.		
Toluene (108-88-3)			
STOT-single exposure	May cause drowsiness or dizziness.		
STOT-repeated exposure :	May cause damage to organs (Neurologic effect, central nervous system) through prolonged or repeated exposure (Inhalation).		
Toluene (108-88-3)			
LOAEL (oral,rat,90 days)	1250 mg/kg body weight Test method EU B.26		
LOAEC (inhalation,rat,gas,90 days)	600 ppmV/6h/day		
NOAEL (oral,rat,90 days)	625 mg/kg body weight Test method EU B.26		
NOAEC (inhalation,rat,gas,90 days)	4522		
NOAEC (inhalation,rat,vapor,90 days)	2.355 mg/l air Test method EU B.29		
Additional information	central nervous system		
STOT-repeated exposure	May cause damage to organs (central nervous system, eyes) through prolonged or repeated exposure (Inhalation).		
Aspiration hazard : May be fatal if swallowed and enters airways.			
Mopar Brake Parts Cleaner			
Aerosol	Aerosol		

12/2/2025 (Revision date) US - en 8/12

Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard (HCS 2024) and the Hazardous Products Regulation (WHMIS 2015 rev 2022)

Mopar Brake Parts Cleaner		
Viscosity, kinematic	< 20 mm²/s	
Hydrocarbon	Yes	
Symptoms/effects	: Aspiration hazard. May be fatal if swallowed and enters airways. Causes eye irritation. Causes skin irritation. May cause drowsiness or dizziness. May cause damage to organs (Neurologic effect, hearing sense) through prolonged or repeated exposure (inhalation). Suspected of damaging fertility or the unborn child.	
Inhalation	: May cause drowsiness or dizziness. At high concentrations, the vapors can be irritating to the respiratory system.	
Skin	: Causes skin irritation.	
Eyes	: Causes serious eye irritation.	
Ingestion	: Aspiration hazard. May be fatal if swallowed and enters airways. May cause gastrointestinal irritation, nausea, vomiting and diarrhea.	
Chronic symptoms	: Suspected of damaging fertility or the unborn child. May cause damage to organs (Neurologic effect, central nervous system) through prolonged or repeated exposure (Inhalation).	

SECTION 12 Ecological information

12.1. Ecotoxicity

Ecology - general : Do not allow product to spread into the environment. Very toxic to aquatic life with long lasting

effects.

Hazardous to the aquatic environment, short-term

(acute

: Not applicable.

Hazardous to the aquatic environment, long-term

: Not applicable.

(chronic)

Acetone (67-64-1)		
NOEC (chronic)	≥ 79 mg/l Daphnia magna (Water flea)	
Toluene (108-88-3)		
LC50 - Fish [1] 5.5 mg/l Oncorhynchus kisutch		
EC50 - Crustacea [1]	3.78 mg/l Ceriodaphnia dubia	
LC50 - Fish [2]	7.63 mg/l Oncorhynchus mykiss (Rainbow trout)	
EC50 72h - Algae [1]	10 mg/l Skeletonema costatum (marine diatom)	
LOEC (chronic) 2.76 mg/l Ceriodaphnia dubia		
NOEC chronic fish 1.39 mg/l Oncorhynchus kisutch		
NOEC chronic crustacea 0.74 mg/l Ceriodaphnia dubia		

12.2. Persistence and degradability

Mopar Brake Parts Cleaner	
Persistence and degradability	No additional information available.
Acetone (67-64-1)	
Persistence and degradability	Readily biodegradable.
Heptane, branched, cyclic and linear (426260-76-6)	
Persistence and degradability	Inherently biodegradable.

Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard (HCS 2024) and the Hazardous Products Regulation (WHMIS 2015 rev 2022)

Toluene (108-88-3)		
Persistence and degradability	Rapidly degradable	
Carbon dioxide (CO2) (124-38-9)		
Persistence and degradability	Biodegradation is not applicable to inorganic compounds.	

12.3. Bioaccumulative potential

No additional information available

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Ozone : Not classified

Fluorinated greenhouse gases : No

SECTION 13 Disposal considerations

Regional waste regulation : Dispose in a safe manner in accordance with local/national regulations.

Waste treatment methods : Dispose in a safe manner in accordance with local/national regulations.

Additional information : Empty containers retain product residue and can be hazardous.

SECTION 14 Transport information

In accordance with DOT / TDG / IMDG / IATA

DOT	TDG	IMDG	IATA
14.1. UN number			
UN1950	UN1950	1950	1950
14.2. Proper Shipping Name			
Aerosols	AEROSOLS	AEROSOLS	Aerosols, flammable
14.3. Transport hazard class(es	s)		
2.1	2.1	2.1	2.1

14.4. Packing group			
Not applicable	Not applicable	Not applicable	Not applicable
14.5. Environmental hazards			
Dangerous for the environment: No	Dangerous for the environment: No	Dangerous for the environment: No Marine pollutant: No	Dangerous for the environment: No
No supplementary information available			

14.6. Transport in bulk

Not applicable

Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard (HCS 2024) and the Hazardous Products Regulation (WHMIS 2015 rev 2022)

14.7. Special precautions for user

DOT

UN-No. (DOT) : UN1950

TDG

UN-No. (TDG) : UN1950 Emergency Response Guide (ERG) Number : 126

IMDG

Special provision (IMDG) : 63, 190, 277, 327, 344, 381, 959

Limited quantities (IMDG) : SP277
Excepted quantities (IMDG) : E0

Packing instructions (IMDG) : P207, LP200
Packing provisions (IMDG) : PP87, L2

EmS-No. (Fire) : F-D - FIRE SCHEDULE Delta - FLAMMABLE GASES

EmS-No. (Spillage) : S-U - SPILLAGE SCHEDULE Uniform - GASES (FLAMMABLE, TOXIC OR CORROSIVE)

Stowage category (IMDG) : None
Stowage and handling (IMDG) : SW1, SW22
Segregation (IMDG) : SG69

IATA

Special provision (IATA) : A145, A167, A802

: E0 PCA Excepted quantities (IATA) : Y203 PCA Limited quantities (IATA) PCA limited quantity max net quantity (IATA) 30kgG PCA packing instructions (IATA) 203 PCA max net quantity (IATA) : 75kg CAO packing instructions (IATA) : 203 CAO max net quantity (IATA) : 150kg ERG code (IATA) : 10L

SECTION 15 Regulatory information

15.1. Federal regulations

Mopar Brake Parts Cleaner	
SARA Section 311/312 Hazard Classes	Refer to Section 2 for OSHA Hazard Classification.

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory.

Chemical(s) subject to the reporting requirements of Section 313 or Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR Part 372.

Toluene CAS-No. 108-88-3 15-25%

Acetone (67-64-1)

CERCLA RQ 5000 lb

Toluene (108-88-3)

Listed on EPA Hazardous Air Pollutant (HAPS)

CERCLA RQ 1000 lb

Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard (HCS 2024) and the Hazardous Products Regulation (WHMIS 2015 rev 2022)

15.2. International regulations

No additional information available

15.3. State regulations



This product can expose you to Toluene, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

Component	State or local regulations
Acetone(67-64-1)	U.S Delaware - Pollutant Discharge Requirements - Reportable Quantities; U.S New Jersey - Right to Know Hazardous Substance List
Toluene(108-88-3)	U.S Delaware - Pollutant Discharge Requirements - Reportable Quantities; U.S New Jersey - Right to Know Hazardous Substance List
Carbon dioxide (CO2)(124-38-9)	U.S New Jersey - Right to Know Hazardous Substance List

SECTION 16 Other information

According to 29CFR 1910.1200 OSHA Hazard Communication Standard (HCS 2024) and the Hazardous Products Regulation (WHMIS 2015 rev 2022)

Revision date : 12/2/2025 Issue date : 12/2/2025

Full text of hazard classes and H-statements	
H222	Extremely flammable aerosol
H229	Pressurized container; may burst if heated
H304	May be fatal if swallowed and enters airways
H315	Causes skin irritation
H319	Causes serious eye irritation
H336	May cause drowsiness or dizziness
H361	Suspected of damaging fertility or the unborn child
H373	May cause damage to organs through prolonged or repeated exposure

Indication of changes:

New SDS.

Safety Data Sheet (SDS), USA

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.